



### GMX Medium Time Lag Glass Tube Fuses

. 5φ x 25 mm ( 0.197 x 0.98 inch )  
 Ampere Rating: 100mA to 20 A  
 Voltage Rating: 250V and less  
**Electrical Characteristics:**  
 210% - 30 Minutes, **Maximum**  
 400% - 0.3 Seconds, **Maximum**  
 1000% - 5 mS Minimum  
**Standards:** DIN 41576



### GMJ Medium Time Lag Glass Tube Fuses

. 5φ x 30 mm ( 0.197 x 1.18 inch )  
 Ampere Rating: 100mA to 20 A  
 Voltage Rating: 250V and less  
**Electrical Characteristics:**  
 210% - 30 Minutes, **Maximum**  
 400% - 0.3 Seconds, **Maximum**  
 1000% - 5 mS Minimum  
**Standards:** DIN 41576



### AWE Fast Acting Glass Tube Fuses

6.3φ x 22.2 mm ( 1/4 x 7/8 inch )  
 Ampere Rating: 10mA to 30 A  
 Voltage Rating: 250V and less  
**Electrical Characteristics:**  
 135% - 1 Hour, **Maximum**  
 200% - 5 Seconds, **Maximum**  
 Pig-Tail Lead(**AWP**): Tinned Copper Wire  
 0.8φ mm- < 13A  
 1.0φ mm- ≥ 13A < 20A  
 1.2φ mm- ≥ 20A  
**Standards:** UL Listed 198G, CSA Certified  
 C22.2N59

AWE AWP



### AAE Fast Acting Glass Tube Fuses

6.3φ x 15.9 mm ( 1/4 x 5/8 inch )  
 Ampere Rating: 63mA to 30 A  
 Voltage Rating: 250V and less  
**Electrical Characteristics:**  
 135% - 1 Hour, **Maximum**  
 200% - 5 Seconds, **Maximum**  
 Pig-Tail Lead(**AAP**): Tinned Copper Wire  
 0.8φ mm- < 13A  
 1.0φ mm- ≥ 13A < 20A  
 1.2φ mm- ≥ 20A

AAE AAP

Approvals: AAP



3.5A and less, 125V



### AXE Fast Acting For Instrument Glass Tube Fuses

6.3φ x 25.4 mm ( 1/4 x 1 inch )  
 Ampere Rating: 10mA to 30A  
 Voltage Rating: 250V and less  
**Electrical Characteristics :**  
 135% - 1 Hour, **Maximum**  
 200% - 10 Seconds, **Maximum**

Approvals ,  
 20A and less



### AXP Fast Acting Glass Tube Fuses With Pig-Tail

6.3φ x 25.4 mm ( 1/4 x 1 inch )  
 Ampere Rating: 10mA to 30A  
 Voltage Rating: 250V and less  
**Electrical Characteristics :**  
 135% - 1 Hour, **Maximum**  
 200% - 10 Seconds, **Maximum**  
 Pig-Tail Lead: Tinned Copper Wire  
 0.8φ mm- < 13A  
 1.0φ mm- ≥ 13A < 20A  
 1.2φ mm- ≥ 20A

Approvals ,  
 10A and less



### GBF Very Fast Acting Ceramic Tube Fuses

. 5φ x 20 mm ( 0.197 x 0.787 inch )  
 Ampere Rating: 1 to 20 A  
 Voltage Rating: 250V and less  
**Electrical Characteristics:**  
 135% - 2 Minutes, **Maximum**  
 250% - 0.2 Seconds, **Maximum**  
**Recommend For Protection:**  
**Solid-State Devices, Semiconductors**



### ABB Super Fast Acting Ceramic Tube Fuses

. 6.3φ x 32 mm ( 1/4 x 1-1/4 inch )  
 Ampere Rating: 1 to 30 A  
 Voltage Rating: 500V and less  
**Electrical Characteristics:**  
 135% - 2 Minutes, **Maximum**  
 250% - 0.2 Seconds, **Maximum**  
**Recommend For Protection:**  
**Solid-State Devices, Semiconductors**