

ABM 8185D/8303D/8602D 直流電源供給器

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- 定電壓源及定電流方式操作
- 過負載及外部逆向輸入保護
- 0.01%高線性穩定度
- 3 1/2 位 0.52 吋紅色 LED 顯示器
- 採用二段式溫度控制散熱風扇速度，以確保散熱品質及降低噪音

型號	8185D	8303D	8602D
OUTPUT VOLTAGE	0~18V	0~30V	0~60V
OUTPUT CURRENT	0~5A	0~3A	0~1.5A
CONSTANT VOLTAGE			
Load Regulation	≤ 0.01%+3mV		
Line Regulation	≤ 0.01%+3mV		
Recovery Time	≤ 50us(50% to 100% Load Change)		
Ripple & Noise	≤ 0.5mVrms		
Temp. Coefficient	≤ 300ppm/°C		
CONSTANT CURRENT			
Load Regulation	≤ 0.06%+4mA		
Line Regulation	≤ 0.06%+4mA		
Ripple & Noise	≤ 1mArms		
INDICATOR METER			
Display Range V Meter	18.00V	30.0V	60.0V
Display Resolution	10mV	100mV	100mV
Display Accuracy	0.2%+5d	0.5%+2d	0.5%+2d
Display Range A Meter	5.00A	3.00A	1.500A
Display Resolution	10mA	10mA	1mA
Display Accuracy	0.5%+2d	0.5%+2d	0.2%+5d
Display Mode	3 1/2 Digits 0.52"red LED Display		
POWER SOURCE	AC 100V,120V, 220V, 240V±10%, 60/50Hz		
OPERATION TEMP. & HUMIDITY	5°C to 40°C, <80%		
STORAGE TEMP. & HUMIDITY	-20°C to 70°C, <80%		
ACCESSORIES	Test Lead x 1, Operation Manual x 1, Power Cord x 1		
DIMENSIONS	213(W) x 88(H) x 394(D) mm		
WEIGHT	6.5kg	6.5kg	6.5kg