

# 直流電源供給器



8306D



8603D



8301HD

## 特點

- 定電壓源及定電流方式操作
- 過負載及外部逆向輸入保護
- 0.01%高線性穩定度
- 3 全位0.52吋紅色LED顯示器
- 採用二段式溫度控制散熱風扇速度，以確保散熱品質及降低噪音

## SPECIFICATIONS

MODEL NAME	8306D	8603D	8301HD
OUTPUT VOLTAGE	0~30V	0~60V	0~30V
OUTPUT CURRENT	0~6A	0~3A	0~10A
CONSTANT VOLTAGE	Load Regulation $\leq 0.01\% + 5mV$ Line Regulation $\leq 0.01\% + 3mV$ Recovery Time $\leq 50\mu s$ (50% to 100% Load Change) Ripple & Noise $\leq 1mV_{rms}$ Temp. Coefficient $\leq 300ppm/^{\circ}C$		
CONSTANT CURRENT	Load Regulation $\leq 0.06\% + 4mA$ Line Regulation $\leq 0.06\% + 4mA$ Ripple & Noise $\leq 3mArms$		
INDICATOR METER	Display Range V Meter Display Resolution Display Accuracy Display Range A Meter Display Resolution Display Accuracy Display Mode		
	30.0V	60.0V	30.0V
	100mV		
	0.5% + 2d		
	6.00A	3.00A	10.00A
	10mA		
	0.5% + 2d		
	3 1/2 Digits 0.52" Red LED Display		
POWER SOURCE	AC 100V, 120V, 220V, 240V $\pm 10\%$ , 60/50Hz		
OPERATION TEMP. & HUMIDITY	5 $^{\circ}C$ to 40 $^{\circ}C$ , <80%		
STORAGE TEMP. & HUMIDITY	-20 $^{\circ}C$ to 70 $^{\circ}C$ , <80%		
ACCESSORIES	Test Lead x1, Operation Manual x1, Power Cord x1		
DIMENSIONS	270(W) x 156(H) x 462(D) mm		
WEIGHT	13kg	13kg	16kg

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)