



Multimeter and Thermometer Accessories

Test Clips




AC20 Spring Loaded Test Clips
(For use with TL22, TL24)
Clamps over a 9/16" (14 mm) bolt head

Safety-grip, spring-loaded alligator clips with a wide .787" (20 mm) jaw opening. 1000V per IEC 1010-1, Overvoltage Category III (Heavy Industrial Rating), 10A rating. One red, one black. UL 1244 Listed. One year warranty




AC85A Large Jaw Alligator Clips
(For use with TL22, TL24)

Large, rugged.
Fully insulated banana-jack alligator clips. Extra strong teeth and new spring design provide superior grip. Extremely rugged. Large .787" (20 mm) opening. 600V per IEC 1010-1, Overvoltage Category III (Heavy Industrial Rating), 10A rating. One red, one black. UL 1244 Listed. One year warranty




AC70A Alligator Clip Set
(For use with TL75)
Economical, general purpose clips

Gold-plated, beryllium-copper, spring contacts accept probe tips from .076" to .084" (1.93 mm to 2.13 mm). Standard jaw opening of .313" (8 mm). 1000V, 10A rating. One red, one black. One year warranty




AC89 Insulation Piercing Clip
(For use with TL22, TL24)

For fast connections when no contact is exposed
Pierces 30 (.25 mm²) to 14 AWG (1.5 mm²) insulated wires with an extremely small, hardened pin, to allow for maximum self-healing of the insulation. 250V, 5A rating. A single probe per package. (For use only with shrouded test leads having standard diameter banana plugs.) One year warranty




AC75 Banana Jack Alligator Clip Set
(For use with TL22, TL24)

General purpose clips for leads with interchangeable tips
Insulated alligator clips with banana jacks. Standard .313" (8mm) jaw opening. Compatible with TL24 test leads. 1000V, 10A rating. Two red, two black. One year warranty




TP20 Test Probes (For use with TL22, TL24)

Extra sharp! Extra strong!
Very sharp, extra-long .750" (19 mm) stainless steel tip. For reaching deep test points or recessed components; will pierce insulation. 1000V per IEC 1010-1, Overvoltage Category III, (Heavy Industrial Rating), 10A rating. One red, one black. Compatible with all test leads having standard, 4mm (.16"), diameter banana plugs, with or without 8mm (.315") safety shrouds. UL 1244 Listed. One year warranty



AC80 Hook-Style Test Clips
(For use with TL22, TL24)
For small wires or circuit board components

Safety-grip, spring-loaded clips with nickel-plated steel hook grip. Hook size is .400" x .080" (10 mm x 2 mm). 1000V per IEC 1010-1, Overvoltage Category III (Heavy Industrial Rating), 3A maximum. One red, one black. UL 1244 Listed. One year warranty



AC83 Flexible Pin-Grabber Test Clips
(For use with TL22, TL24)
For gripping around extremely small contact points.

Safety-grip, spring-loaded pin-grabber hooks for use with test points in close contact areas. Flexible shaft is 4" (100 mm), grabber extends .375" (9.5 mm). 1000V per IEC 1010-1, Overvoltage Category III (Heavy Industrial Rating), 1A rating. One red, one black. UL 1244 Listed. One year warranty

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)