

SANWA Analog Multitester AU-31 指針錶



General Information

- High internal resistance
- Auto-range function
- Automatic polarity function
- Auto zero ohm adjustment
- Auto power off
- Inner battery check range
- Series condenser built in circuit

Standard Accessories Included

- Test lead (TL-61G) x 1set
- Spare fuse (0.3A/250V - 20mm) x 1

Optional Accessories

- High voltage probe (HV-50)
- Carrying case (C-SP)
- For more information about accessories

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

AU-31	Measuring range	Accuracy
DCV	±300m (approx. 1MΩ/V) /3/12/60/300/1000V (10MΩ/V)	±3% of full scale
ACV	300m (approx. 1MΩ/V) /3/12/60/300/1000V (10MΩ/V)	±3% of full scale
DCA	±300m/3A	±3% of full scale
ACA	300m/3A	±3% of full scale
Resistance	20k/200k/2M/20M/200MΩ	±3% of arc
dB	-9/+11/+23/+37/+51/+62dB	—
Bandwidth	40~10kHz (0.3V : ±5%) 40~1kHz (3V~ : ±4%)	
Battery	R03×4	
Fuse	φ5.2×20mm (250V/0.5A)	
Size / Weight	H48×W110×D124mm/approx. 290g	
Standard accessories included	Test lead (TL-61), Instruction manual	

The value in () at DCV and ACV is input resistance.