




勝特力材料 886-8-5753170  
 勝特力電子(上海) 86-21-54151736  
 勝特力電子(深圳) 86-755-83298787  
<http://www.100y.com.tw>

REV 版次	DESCRIPTION 說明	ENG 設計人	APPROVE 審核
-----------	-------------------	------------	---------------



"x"	LED Color
R	Red
G	Green
Y	Yellow
O	Orange
B	Blue
W	White

**SPECIFICATIONS:**

- Contact Rating: 3A @ 250VAC.
- Electrical Life: 50,000cycles.
- Contact Resistance: 50m-ohms max (initial).
- Insulation Resistance: 1,000M-ohms min @ 500VDC.
- Dielectric Strength: 2,000V RMS 50~60Hz.
- Operating Temperature: -20°C ~ +70°C.
- Switching Circuit: ON-MOM.
- IP Class: IP67 protection.
- Torque: 5~14Nm max. applied to nut.
- Operating Force: 5.5N max.

**MATERIALS:**

- Bushing & Button: Refer to below table
- Contact: Silver alloy.
- Nut: Nickel plated brass.
- Base: PBT.

Code	Bushing & Button Material
B3	Nickel plated brass with varnished polished
B31	Gold plated brass with varnished polished
B32	Stainless steel with varnished polished

ITEM NO. 料號 AV02L-B3-M3-FR-B

USED 規格	AV	
FINISH 處理		
SCALE 比例	2 / 1 (UNIT 單位 (mm))	
TITLE 名稱	Anti-Vandal Switch	
ENG NO. 料號	AV02L-B3(B3x)-M3-FR-x	SIZ 規格
FILE NAME 檔案名稱	AV02LB3M3FRD	REV 版次
	1 / 1	1