


Specification :

- **Conductor :**
Solid and Stranded Tinned Copper
- **Insulation :**
FEP TEFLON
- **Wall Thickness :**
0.33mm
- **Temperature Rating :**
UL 200° C
- **Voltage Rating :**
UL 300 V
- **Colors :**
White, Red, Orange, Yellow, Green,
Blue, Black, Gray, Brown, Violet



FEP TEFLON **HIGH TEMP. WIRE**



UL FILE No. E208889 UL AWM Style # 1332

Style	Conductor			Insulation Thickness	Overall Diameter
	AWG	Stranding No./mm	Diameter	mm	mm
UL 1332	30	1 / 0.254	0.25	0.33	0.91
		7/0.102	0.30	0.33	
		19/0.064	0.98	0.33	
	28	1 / 0.32	0.32	0.33	0.98
		7 / 0.127	0.32	0.33	1.04
	28	7 / 0.127	0.38	0.33	1.06
		1 / 0.404	0.40	0.33	1.14
	26	7 / 0.16	0.48	0.33	1.17
		1 / 0.511	0.51	0.33	1.27
	24	7 / 0.203	0.61	0.33	1.30
		1 / 0.643	0.64	0.33	1.42
	22	7 / 0.254	0.76	0.33	1.47
		1 / 0.813	0.81	0.33	1.62
	20	7 / 0.32	0.96	0.33	1.86
		7 / 0.404	1.2	0.33	1.86
	18	16 / 0.254	1.2	0.33	2.16
		19 / 0.287	1.5	0.33	2.16
	16	26 / 0.254	1.5	0.33	
		offer by requested			

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)