


一、型号及含义




辅助功能: 抗浪涌-L、抗干扰K6: $\geq 6V$ 、K10: $\geq 10V$

颜色: R-红色、Y-黄色、G-绿色、B-蓝色、W-白色

额定电压(AC/DC): 6-6V、12-12V、24-24V、110-110V、220

品种: X-新型、XSG-新型闪光型

灯珠代号



二、技术参数

型号	额定工作电压 (V)	发光颜色	波长 (nm)	型号参数		测试电压 (VAC/DC)	工作电压范围 (VAC/DC)	使用环境 (°C)
				发光亮度 (cd/m ²)	工作电流 (mA)			
BA9S-X BA9S-XSG	6	R	620	2080	≤ 20	6	6~8	-20~50
		Y	585	2800	≤ 20			
		G	525	1700	≤ 20			
		B	470	900	≤ 20			
		W	X=0.31 Y=0.32	2500	≤ 20			
	12	R	620	2000	≤ 20	12	12~13.2	
		Y	585	2700	≤ 20			
		G	525	1500	≤ 20			
		B	470	850	≤ 20			
		W	X=0.31 Y=0.32	2450	≤ 20			
	24	R	620	2000	≤ 20	24	24~26.4	
		Y	585	2700	≤ 20			
		G	525	1500	≤ 20			
		B	470	850	≤ 20			
		W	X=0.31 Y=0.32	2450	≤ 20			
	110	R	620	600	≤ 5	110	110~130	
		Y	585	950	≤ 5			
		G	525	900	≤ 5			
		B	470	500	≤ 5			
		W	X=0.31 Y=0.32	2300	≤ 5			
220	R	620	460	≤ 3	220	220~240		
	Y	585	550	≤ 3				
	G	525	850	≤ 3				
	B	470	330	≤ 3				
	W	X=0.31 Y=0.32	1200	≤ 3				