

INSULATED BULLET DISCONNECTORS

1. MAXIMUM ELECTRICAL RATING :

75 °C 300 VOLTS MAX

2. MAXIMUM ELECTRIC CURRENT :


22~16 AWG / 0.5~1.5 mm² : 10 AMPERE

16~14 AWG / 1.5~2.5 mm² : 15 AMPERE

12~10 AWG / 4 ~ 6 mm² : 24 AMPERE

3. TERMINAL MATERIAL : BRASS

4. INSULATED MATERIAL : VINYL (PVC)



WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)					
		B	F	L	E	D	d1
22~16 AWG 0.5~1.5 mm ²	BD1-4V	.157 (4.0)	.335 (8.5)	.827 (21.0)	.394 (10.0)	.157 (4.0)	.067 (1.7)
16~14 AWG 1.5~2.5 mm ²	BD2-4V						.177 (4.5)
	BD2-5V	.197 (5.0)					
12~ 10 AWG 4~6 mm ²	BD5-5V						.906 (23.0)

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw


圖號 . DRAWING . NO : FP3BD-V

品名 NAME : BULLET

ITEM NO. :

校訂版次 REVISIONS

版次	記述 DESCRIPTION	DATE	核可



NOTE:

MAXIMUM ELECTRICAL RATING: 75 °C 300 VOLTS

BD1-4V

1. WIRE RANGE: AWG 22-16/0.5-1.5mm²: 10 AMPERE MAX.

2. INSULATED COLOR: RED

BD2-4V BD2-5V


1. WIRE RANGE: AWG 16-14/1.5-2.5mm²: 15 AMPERE MAX.

2. INSULATED COLOR: BLUE

BD5-5V

1. WIRE RANGE: AWG 12-10/4-6mm²: 24 AMPERE MAX.

2. INSULATED COLOR: YELLOW



產品編號 ITEM NO.	B ±0.20	F ±0.30	L ±1.00	E ±0.60	D ±0.30	d1 ±0.20
BD1-4V	4.0	8.5	21.0	10.0	4.0	1.7
BD2-4V	4.0		21.0	10.0	4.5	2.3
BD2-5V	5.0		21.0	10.0	4.5	2.3
BD5-5V	5.0		23.0	12.5	5.5	3.4

認可 APPROVALS

第三視角
THIRD VIEW

MATERIAL

單位 UNITE

製圖 DRAFT: Den

INSULATION: VINYL

m / m


設計 DESIGN: 劉'r

MATERIAL: BRASS

比例 SCALE

核可 CHECKED: Chen

TIN PLATING



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)