BRIGHT LED ELECTRONICS CORP.

BL-B2134-AT


Features:

- 1. Chip material: GaP/GaP
- 2. Emitted color : Green
- 3 Lens Appearance : Green Diffused
- 4. Low power consumption.
- 5. High efficiency.
- 6. Versatile mounting on P.C. Board or panel.
- 7. Low current requirement.
- 8. 5mm diameter package.
- 9. This product don't contained restriction substance, compliance ROHS standard.

Applications:

- 1. TV set
- 2. Monitor
- 3. Telephone
- 4. Computer
- 5. Circuit board

Package dimensions:



Notes:

- 1. All dimensions are in millimeters (inches).
- 2. Tolerance is ±0.25mm (0.01^{*}) unless otherwise specified.
- Lead spacing is measured where the leads emerge from the package.
- 4. Specifications are subject to change without notice.

勝特力材料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw

Parameter	Symbol	Rating	Unit			
Power Dissipation	Pd	80,00	mW			
Forward Current	OV.COF TW	30	mA			
Peak Forward Current*1	1001 IFP N.TV	150	mA			
Reverse Voltage	VR ONL	5.100 COM.1	V			
Operating Temperature	Topr	-40℃~85℃				
Storage Temperature	Tstg	-40°C~100°C				
Soldering Temperature	Tsol	260℃max(for 5 seconds)				
Hand Soldering Temperature	Tsol	350°C max(for 3 seconds)				

*¹Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.

Ver.1.0 Page: 1 of 3

● Absolute Maximum Ratings(Ta=25°C)

BRIGHT LED ELECTRONICS CORP.

lectrical and optical characteristics(Ta=25℃)								
Parameter	Symbol	Condition	Min.	Тур.	Max.	Uni		
Forward Voltage	VF	I _F =20mA	MAN	2.2	2.6	V		
C Luminous Intensity	Iv v.	I _F =20mA	WW	40	WIM	mco		
Reverse Current	IR	V _R =5V	- WV	1707.0	100	μΑ		
Peak Wave Length	λp	I _F =20mA	- 1	568	COM.TW	nm		
Dominant Wave Length	λd	I _F =20mA	560	100	576	nm		
Spectral Line Half-width	Δλ	I _F =20mA	- 17	30	N.COm	nm 🕅		
Viewing Angle	20 _{1/2}	I _F =20mA	- 17	35	NY.COM	deg		

Typical Electro-Optical Characteristics Curves

