


# DATA SHEET



勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## **BYV26 series** Fast soft-recovery controlled avalanche rectifiers

Product specification  
Supersedes data of February 1994

1996 May 30

## Fast soft-recovery controlled avalanche rectifiers

## BYV26 series


### FEATURES

- Glass passivated
- High maximum operating temperature
- Low leakage current
- Excellent stability
- Guaranteed avalanche energy absorption capability
- Available in ammo-pack.

### DESCRIPTION

Rugged glass SOD57 package, using a high temperature alloyed construction.

This package is hermetically sealed and fatigue free as coefficients of expansion of all used parts are matched.



### LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{RRM}$	repetitive peak reverse voltage				
	BYV26A		–	200	V
	BYV26B		–	400	V
	BYV26C		–	600	V
	BYV26D		–	800	V
	BYV26E		–	1000	V
	BYV26F BYV26G		–	1200 1400	V V
$V_R$	continuous reverse voltage				
	BYV26A		–	200	V
	BYV26B		–	400	V
	BYV26C		–	600	V
	BYV26D		–	800	V
	BYV26E		–	1000	V
	BYV26F BYV26G		–	1200 1400	V V
$I_{F(AV)}$	average forward current	$T_{tp} = 85\text{ }^{\circ}\text{C}$ ; lead length = 10 mm; see Figs 2 and 3;			
	BYV26A to E BYV26F and G	averaged over any 20 ms period; see also Figs 10 and 11	–	1.00 1.05	A A
$I_{F(AV)}$	average forward current	$T_{amb} = 60\text{ }^{\circ}\text{C}$ ; PCB mounting (see Fig.19); see Figs 4 and 5;			
	BYV26A to E BYV26F and G	averaged over any 20 ms period; see also Figs 10 and 11	–	0.65 0.68	A A
$I_{FRM}$	repetitive peak forward current	$T_{tp} = 85\text{ }^{\circ}\text{C}$ ; see Figs 6 and 7			
	BYV26A to E BYV26F and G		–	10.0 9.6	A A

Fast soft-recovery  
 controlled avalanche rectifiers

BYV26 series

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$I_{FRM}$	repetitive peak forward current BYV26A to E BYV26F and G	$T_{amb} = 60\text{ }^{\circ}\text{C}$ ; see Figs 8 and 9	–	6.0	A
$I_{FSM}$	non-repetitive peak forward current	$t = 10\text{ ms}$ half sine wave; $T_j = T_{j\text{ max}}$ prior to surge; $V_R = V_{RRM\text{ max}}$	–	30	A
$E_{RSM}$	non-repetitive peak reverse avalanche energy	$I_R = 400\text{ mA}$ ; $T_j = T_{j\text{ max}}$ prior to surge; inductive load switched off	–	10	mJ
$T_{stg}$	storage temperature		–65	+175	$^{\circ}\text{C}$
$T_j$	junction temperature	see Figs 12 and 13	–65	+175	$^{\circ}\text{C}$

**ELECTRICAL CHARACTERISTICS**

$T_j = 25\text{ }^{\circ}\text{C}$  unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_F$	forward voltage BYV26A to E BYV26F and G	$I_F = 1\text{ A}$ ; $T_j = T_{j\text{ max}}$ ; see Figs 14 and 15	–	–	1.3	V
$V_F$	forward voltage BYV26A to E BYV26F and G	$I_F = 1\text{ A}$ ; see Figs 14 and 15	–	–	2.50	V
$V_{(BR)R}$	reverse avalanche breakdown voltage BYV26A BYV26B BYV26C BYV26D BYV26E BYV26F BYV26G	$I_R = 0.1\text{ mA}$	300 500 700 900 1100 1300 1500	– – – – – – –	– – – – – – –	V V V V V V V
$I_R$	reverse current	$V_R = V_{RRM\text{ max}}$ ; see Fig.16	–	–	5	$\mu\text{A}$
		$V_R = V_{RRM\text{ max}}$ ; $T_j = 165\text{ }^{\circ}\text{C}$ ; see Fig.16	–	–	150	$\mu\text{A}$
$t_{rr}$	reverse recovery time BYV26A to C BYV26D and E BYV26F and G	when switched from $I_F = 0.5\text{ A}$ to $I_R = 1\text{ A}$ ; measured at $I_R = 0.25\text{ A}$ ; see Fig.20	– – –	– – –	30 75 150	ns ns ns
$C_d$	diode capacitance BYV26A to C BYV26D and E BYV26F and G	$f = 1\text{ MHz}$ ; $V_R = 0\text{ V}$ ; see Figs 17 and 18	– – –	45 40 35	– – –	pF pF pF

Fast soft-recovery  
 controlled avalanche rectifiers

BYV26 series

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$\left  \frac{dI_R}{dt} \right $	maximum slope of reverse recovery current	when switched from $I_F = 1$ A to $V_R \geq 30$ V and $dI_F/dt = -1$ A/ $\mu$ s; see Fig.21	—	—	7	A/ $\mu$ s
	BYV26A to C		—	—	6	A/ $\mu$ s
	BYV26D and E		—	—	5	A/ $\mu$ s
	BYV26F and G		—	—	5	A/ $\mu$ s

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j-tp}$	thermal resistance from junction to tie-point	lead length = 10 mm	46	K/W
$R_{th\ j-a}$	thermal resistance from junction to ambient	note 1	100	K/W





Note

1. Device mounted on an epoxy-glass printed-circuit board, 1.5 mm thick; thickness of Cu-layer  $\geq 40$   $\mu$ m, see Fig.19. For more information please refer to the "General Part of associated Handbook".

Fast soft-recovery  
 controlled avalanche rectifiers



BYV26 series

GRAPHICAL DATA





Fast soft-recovery controlled avalanche rectifiers

BYV26 series







Fast soft-recovery  
controlled avalanche rectifiers

BYV26 series



Fast soft-recovery  
 controlled avalanche rectifiers





BYV26 series








Fast soft-recovery  
 controlled avalanche rectifiers

BYV26 series



Fast soft-recovery  
 controlled avalanche rectifiers

BYV26 series



Fast soft-recovery  
controlled avalanche rectifiers

BYV26 series





Fig.21 Reverse recovery definitions.

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**Fast soft-recovery  
 controlled avalanche rectifiers**

**BYV26 series**

**PACKAGE OUTLINE**



**DEFINITIONS**

<b>Data Sheet Status</b>	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
<b>Limiting values</b>	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
<b>Application information</b>	
Where application information is given, it is advisory and does not form part of the specification.	

**LIFE SUPPORT APPLICATIONS**

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.