



**8762 Paired - Single-Pair Cable**

		<p><b>For more information please call</b>  <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	--	---

**Description:**

20 AWG stranded (7x28) TC conductors, polyethylene insulation, twisted pair, overall Beldfoil® shield (100% coverage), 20 AWG stranded TC drain wire, PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Pairs	1
Total Number of Conductors	2
AWG	20
Stranding	7x28
Conductor Material	TC - Tinned Copper

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**INSULATION:**

Insulation Material	PE - Polyethylene
Nom. Insulation Wall Thickness	.016 in.
Lay Length	1.5 in.
Twists/ft.	8

**Pair Color Code Chart :**

Number	Color
1	Black & Clear

**OUTER SHIELD:**

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape w/Shorting Fold
Outer Shield % Coverage	100 %

**OUTER SHIELD DRAIN WIRE :**

Outer Shield Drain Wire AWG	20
Outer Shield Drain Wire Stranding	7x28
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------



**8762 Paired - Single-Pair Cable**

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Outer Jacket Nominal Wall Thickness .028 in.

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter .204 in.

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range -20°C To +60°C  
 UL Temperature Rating 60°C (UL AWM Style 2092)  
 Bulk Cable Weight 21.2 lbs/1000 ft.  
 Max. Recommended Pulling Tension 46 lbs.  
 Min. Bend Radius (Install) 2 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification CM  
 CEC/C(UL) Specification CM  
 AWM Specification UL Style 2092 (300 V 60°C)  
 EU CE Mark (Y/N) Yes  
 EU RoHS Compliant (Y/N) Yes  
 EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

**FLAME TEST:**

UL Flame Test UL1685 UL Loading

**PLENUM/NON-PLENUM:**

Plenum (Y/N) N

**ELECTRICAL CHARACTERISTICS:**

Nom. Characteristic Impedance 56 Ohms  
 Nom. Inductance .18 µH/ft  
 Nom. Capacitance Conductor to Conductor @ 1 KHz 27 pF/ft  
 Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz 49 pF/ft  
 Nom. Conductor DC Resistance @ 20 Deg. C 9.5 Ohms/1000 ft  
 Max. Operating Voltage - UL 300 V RMS  
 Max. Recommended Current 3.9 Amps per conductor @ 25°C

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8762 060100	2 #20 PE FS PVC	100	3.2	CHROME	
8762 0601000	2 #20 PE FS PVC	1000	23	CHROME	C
8762 06010000	2 #20 PE FS PVC	10000	240	CHROME	C Y

**8762 Paired - Single-Pair Cable**

8762 0602000	2 #20 PE FS PVC	2000	46	CHROME	C
8762 060250	2 #20 PE FS PVC	250	6.25	CHROME	
8762 060500	2 #20 PE FS PVC	500	12	CHROME	C
8762 060U1000	2 #20 PE FS PVC	U1000	23	CHROME	
8762 060U500	2 #20 PE FS PVC	U500	12	CHROME	

C = CRATE REEL PUT-UP.

Y = FINAL PUT-UP LENGTH MAY VARY -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

Revision Number: 1      Revision Date: 07-27-2005

© 2005 Belden Wire & Cable Company  
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)