


8774 Paired - CM Rated Cable

勝特力材料 886-3-5753170
 胜特力电子(上海) 86-21-54151736
 胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



For more information please call
1-800-Belden1

See Put-ups and Colors

Color Code Chart : No. 3 for Paired Cables (Belden Standard).pdf

Description:

22 AWG stranded (7x30) tinned copper conductor, polypropylene insulation, twisted pairs individually shielded with Beldfoil® (100% coverage), overall PVC jacket and 22 AWG stranded tinned copper drain wire.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

| | |
|----------------------------|--------------------|
| Number of Pairs | 9 |
| Total Number of Conductors | 18 |
| AWG | 22 |
| Stranding | 7x30 |
| Conductor Diameter | .030 in. |
| Conductor Material | TC - Tinned Copper |

INSULATION:

| | |
|---------------------|--------------------|
| Insulation Material | PP - Polypropylene |
| Insulation Diameter | .050 in. |
| Lay Length | 1.75 in. |
| Twists/ft. | 6.85 |

Pair Color Code Chart :

| Number | Color | Number | Color |
|--------|----------------|--------|----------------|
| 1 | Black & Red | 6 | Black & Brown |
| 2 | Black & White | 7 | Black & Orange |
| 3 | Black & Green | 8 | Red & White |
| 4 | Black & Blue | 9 | Red & Green |
| 5 | Black & Yellow | | |

INNER SHIELD:

| | |
|----------------------------------|------------------------------|
| Inner Shield Material Trade Name | Beldfoil® (Z-Fold®) |
| Inner Shield Type | Tape |
| Inner Shield Material | Aluminum Foil-Polyester Tape |
| Inner Shield % Coverage | 100 % |

8774 Paired - CM Rated Cable

| | |
|--|--------------------|
| Inner Shield Drain Wire AWG | 22 |
| Inner Shield Drain Wire Stranding | Stranded |
| Inner Shield Drain Wire Conductor Material | TC - Tinned Copper |

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

OUTER SHIELD:

| | |
|-----------------------|------------|
| Outer Shield Material | Unshielded |
|-----------------------|------------|

OUTER JACKET:

| | |
|-----------------------|--------------------------|
| Outer Jacket Material | PVC - Polyvinyl Chloride |
|-----------------------|--------------------------|

OVERALL NOMINAL DIAMETER:

| | |
|--------------------------|----------|
| Overall Nominal Diameter | .417 in. |
|--------------------------|----------|

MECHANICAL CHARACTERISTICS:

| | |
|----------------------------------|--------------------------|
| Operating Temperature Range | -20°C To +80°C |
| UL Temperature Rating | 80°C (UL AWM Style 2919) |
| Bulk Cable Weight | 108.6 lbs/1000 ft. |
| Max. Recommended Pulling Tension | 230 lbs. |
| Min. Bend Radius (Install) | 4.3 in. |

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

| | |
|---------------------------------------|---------------------------|
| NEC/(UL) Specification | CM |
| CEC/C(UL) Specification | CM |
| AWM Specification | UL Style 2919 (30 V 80°C) |
| EU CE Mark (Y/N) | Yes |
| EU RoHS Compliant (Y/N) | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |

FLAME TEST:

| | |
|---------------|-------------------|
| UL Flame Test | UL1685 UL Loading |
|---------------|-------------------|

PLENUM/NON-PLENUM:

| | |
|--------------|---|
| Plenum (Y/N) | N |
|--------------|---|

ELECTRICAL CHARACTERISTICS:

| | |
|--|-------------------|
| Nom. Characteristic Impedance | 50 Ohms |
| Nom. Inductance | .018 µH/ft |
| Nom. Capacitance Conductor to Conductor @ 1 KHz | 30 pF/ft |
| Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz | 55 pF/ft |
| Nominal Velocity of Propagation | 66 % |
| Nom. Conductor DC Resistance @ 20 Deg. C | 15 Ohms/1000 ft |
| Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C | 10.6 Ohms/1000 ft |

8774 Paired - CM Rated Cable

| | |
|-----------------------------|--|
| Max. Operating Voltage - UL | 30 V RMS (UL AWM Style 2919), 300 V RMS (CM) |
| Max. Recommended Current | 1.4 Amps per conductor @25°C |

PUT-UPS AND COLORS:

| Item | Description | Put-Up (ft.) | Ship Weight (lbs.) | Jacket Color | Notes |
|--------------|-------------------------|--------------|--------------------|--------------|-------|
| 8774 060100 | 9 FS PR #22 HDPE PVC | 100 | 11.6 | CHROME | |
| 8774 0601000 | 9 FS PR #22 HDPE PVC | 1000 | 115 | CHROME | C |
| 8774 060250 | 9 FS PR #22 HDPE PVC | 250 | 29.75 | CHROME | C |
| 8774 060500 | 9 FS PR #22 HDPE PVC | 500 | 58 | CHROME | C |

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 08-10-2005

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)