

Detailed Specifications & Technical Data



9912 Hook-up/Lead - UL AWM Style 1015

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	12
Stranding	65x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.030 in.

OVERALL:

Overall Nominal Diameter	.158 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	1015
UL Rating	600 V, 105°C
CSA Type	TEW
CSA Rating	600 V, 105°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005
Other Specification	JQA-F-

FLAME TEST:

UL Flame Test	VW-1
---------------	------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

Detailed Specifications & Technical Data

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



9912 Hook-up/Lead - UL AWM Style 1015

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9912 001100	12 STR PVC BRN	100	3.7	BROWN	
9912 0012000	#12 STR PVC BRN	2000	60	BROWN	C
9912 001250	12 STR PVC BRN	250	7.75	BROWN	
9912 002100	12 STR PVC RED	100	3.7	RED	
9912 0022000	002 STR PVC RED	2000	60	RED	C
9912 002250	12 STR PVC RED	250	7.75	RED	
9912 003100	12 STR PVC ORG	100	3.7	ORANGE	
9912 0032000	#12 STR PVC ORG	2000	60	ORANGE	C
9912 003250	12 STR PVC ORG	250	7.75	ORANGE	
9912 004100	12 STR PVC YEL	100	3.7	YELLOW	
9912 0042000	#12 STR PVC YEL	2000	60	YELLOW	C P
9912 004250	12 STR PVC YEL	250	7.75	YELLOW	
9912 005100	12 STR PVC D GRN	100	3.7	GREEN, DARK	
9912 0052000	#12 STR PVC DGRN	2000	60	GREEN, DARK	C
9912 005250	12 STR PVC D GRN	250	7.75	GREEN, DARK	
9912 007100	#12 STR PVC VIO	100	3.7	VIOLET	
9912 008100	#12 STR PVC GRY	100	3.7	GRAY	
9912 008250	#12 STR PVC GRY	250	7.75	GRAY	
9912 009100	12 STR PVC WHT	100	3.7	WHITE	
9912 0092000	#12 STR PVC WHT	2000	60	WHITE	C
9912 009250	12 STR PVC WHT	250	7.75	WHITE	
9912 010100	12 STR PVC BLK	100	3.7	BLACK	
9912 0102000	#12 STR PVC BLK	2000	60	BLACK	C
9912 010250	12 STR PVC BLK	250	7.75	BLACK	
9912 013100	12 STR PVC D BLU	100	3.7	BLUE, DARK	
9912 0132000	#12 STR PVC DBLU	2000	60	BLUE, DARK	P

Detailed Specifications & Technical Data

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



9912 Hook-up/Lead - UL AWM Style 1015

9912 013250	12 STR PVC D BLU	250	7.75	BLUE, DARK	
-------------	------------------	-----	------	------------	--

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1

Revision Date: 04-26-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.