
WY.100Y.COM.TW 勝特力材料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www. 100y. com. tw

100Y.COM.TW

OMTW

WWW.100Y.COM.T

WWW.100Y.COM.TW



WW.100X.COM.TW W.100Y.COM. V.COM.TW 24 Pin Machine Tooled Solder Tail Low Profile Socket

WHLoc MFG	MFG Par	t#0	Description
ONLEW	24MLP	N.C	Socket, IC, 24Pin, Gold, Machine Tooled Solder Tail, Low Profile, 0.6"W
Product Features	WWW.IU	.Y00	CONTRA MANNING TO THE CONTRACT
Contact Platting:	WWW.	Gold	l; Tin plated leads
Material:	WWW		/llium copper or phosphor bronze
Contact Current:		3A	COMPT NAME OF THE OWNER
Contact Resistance:		Less	than 5m Ohm
Dielectric Withstanding Voltage:		300	Vrms
Insulation Resistance:		Grea	ater than 1,000M Ohm
Insulator:			s-filled polyester or glass-filled polyest
Sleeve Material:		Bras	S. 1002 OM.T
Lead Length:		0.17	7", 100Y. WIN
Pins:		22	N MILLON TW WW
Body Height:		0.11	7" R. CON. TW WY
Width:		0.60	
Weight (lbs.):		0.00	