



PIN NO.	D	PIN NO.	D
6	19.30	22	55.90
8	20.30	24	61.00
10	25.40	28	71.10
14	35.50	30	76.20
16	40.60	32	81.30
18	45.70	36	91.40
20	50.80	40	101.60

SPECIFICATIONS

MATERIAL

Sleeve: Brass Gold over Nickel plated
 Clip: Beryllium Copper Gold over Nickel plated

ELECTRICAL

Contact Rating 1 ADC Max.
 Contact Resistance 10 m Max.
 Insulation Resistance 106 M Min. at 100 VDC
 Dielectric Strength 1000 VAC Min. for 1 minute
 Capacitance between adjacent pin 0.9 pF Max.

MECHANICAL AND ENVIRONMENTAL

Temperature Rating:
 Operating -55 to +125
 Life cycle with insertion and withdrawal :
 100 operating cycles Min.
 Humidity: 90-95%RH, 40 for 96 Hrs.
 Vibration: per MIL-STD-202F METHOD 204D
 Solderability: per MIL-STD-202F METHOD 208D
 Soldering Heat: 260± 5 for 5± 1 seconds

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

制表日: 2003/08/26

DRAWING. APPROVED

APPD. CKD.

TOLERANCE

PART NO.

REV.

± 0.3

A

PART NAME
 2.54mm SIP Socket
 Wire-Wrap Pin /Single Row