

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

導電銅/鋁箔膠帶

Conductive Copper/Aluminium

特点 Features

高性能的導電銅/鋁箔膠帶，覆以感壓性導電膠，使其上具有極佳的導電性和屏蔽效果，不同的形狀尺寸能滿足廣泛屏蔽設計上的需求。

With high conductance, the Copper/Aluminium Tape has well shielding effectiveness. The Copper/Aluminium Tape can be customized as any sizes and shapes you need. It is satisfyingly be used in EMI shielding technology.

用途 Application

適用於EMI電磁波遮蔽,靜電放電,具柔性適用於接地連接用。

Can be flexible used for EMI shielding, electro-magnetic grounding, static electricity grounding, etc.

构造 Construction



材质/物性

材料物質 Article Matter	--	壓延鋁箔	壓延銅箔
厚度 Thickness	mm	0.035±0.01	0.025±0.005
基重 Basic Weight	g/m ²	95±7	225
抗張力 Tensile Strength	Kg/25mm	<5	<2
伸長率 Elongation	%	<5	2
表面阻抗 Surface Resist	Ω/□	≤0.06	≤0.03
電磁波遮蔽率 EMI Effectiveness (E-field.dB)	500MHz/dB	>60	>80
顏色 Color	--	銀白色	亮黃銅色

