



Product Description

Plastic safe lubricant, penetrant and corrosion inhibitor that helps prevent electrical moisture penetration, humidity, condensation or corrosion. Restores resistance values and leakage.

Product Specifications

Food Grade Type	H2
H2 Type	Electrical
Electrical Type	Moisture Displacing
Applications	Connectors, relays, circuit breakers, transducers, motors, generators, controls, instruments, assemblies, electronics, alarm systems, stampings, castings, gears, weld rod, wire, fixtures, die chucks.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Multi-Purpose Precision Lubricant Plastic Safe
Net Fill	11 Wt Oz
UPC Code	0 78254 02005 1
Unit Dimensions-Inches	7.75H x 2.63W x 2.63L
Units Per Case	12
Case Dimensions-Inches	8.69H x 11.31W x 8.44L
Cases Per Pallet	133
12 of 5 Code	30078254020052
Appearance	Amber
Odor	Pleasant
Base Type	Petroleum
Flashpoint - TCC Method	195°F
Specific Gravity	0.8127
VOC %	None
VOC G/L	None
VOC Lbs./Gal.	None
Flammable	Yes
Plastic Safe	Yes
Film Type	Wet
Film Thickness	0.025 to 0.075 Mil
Evaporation Rate	Slow
Dielectric Strength	30,500 Volts/Mil
Working Temp [Degrees F]	Max 250°F
Propellant	Carbon Dioxide
NSF Registered	Yes
NSF Number	017224
Federal Specification Number	O-W-1284B Cl. 1 Type II
Federal Specification Number	V-V-P-216
Aerosol Flammability Level	III
DOT Proper Shipping Name	Consumer Commodity, ORM-D
VOC Compliant for CA & OTC	Yes
Removal (How To)	Remove with petroleum products, mineral spirits, degreaser or contact cleaner.
NSF Category Code	H2

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)