



### Product Description:

Non-curing silicone compound used for electrical sealing, lubricating, protecting and insulating. Waterproofs electrical connections and components. Improves electrical performance in adverse weather conditions.

### Product Specifications:

Applications	Electrical panels, outdoor lighting, scoreboards, traffic lights, high vol poles, transformers, disconnects, switching mechanisms, electrical cor spark plugs, battery terminals, fasteners, o-rings, rubber and plastic p
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Non-Curing Silicone Compound for Sealing, Lubricating, Protecting, Ar Insulating Electrical Components
Net Fill	10.5 Wt Oz
UPC Code	0 78254 02083 9
Unit Dimensions-Inches	7.75H x 2.63W x 2.63L
Units Per Case	12
Case Dimensions-Inches	8.69H x 11.31W x 8.44L
Cases Per Pallet	133
I 2 of 5 Code	30078254020830
Appearance	Translucent to Opaque Gel Paste
Odor	Solvent
Base Type	Silicone
Flashpoint - TCC Method	<20° F
Specific Gravity	0.6510
VOC %	90
VOC G/L	585
VOC Lbs./Gal.	4.88
Flammable	Yes
Plastic Safe	Safe on Most Plastics
Film Type	Wet
Evaporation Rate	Fast
Working Temp [Degrees F]	Max 400 °F
Propellant	Hydrocarbon
NSF Registered	Yes
NSF Number	130626
Military Specification Number	Mil-S-8660 (DM-3)
Federal Specification Number	FDA-CFR-21-175.300, FDZ-CFR-21-178.3570
Aerosol Flammability Level	III
DOT Proper	Consumer Commodity, ORM-D

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Shipping Name	
VOC Compliant for CA & OTC	Not Regulated
NSF Category Code	H1

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)