



Product Description:

Polyurethane coating that insulates electrical equipment and seals out water and moisture. Clear formula allows for visualization of equipment; red provides a striking contrast.

Product Specifications:

Applications	On motor windings, terminals, bus bars, commutator ends, stator coils, and PC boards
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Urethane Coating
Net Fill	11 Wt Oz
UPC Code	0 78254 18410 4
Unit Dimensions-Inches	7.75H x 2.63W x 2.63L
Units Per Case	12
Case Dimensions-Inches	8.5H x 8.25W x 11L
Cases Per Pallet	133
I 2 of 5 Code	30078254184105
Appearance	Red-Brown Liquid
Odor	Pleasant, Faintly Aromatic
Flashpoint - TCC Method	<20°F
Specific Gravity	0.845
VOC %	61.5
VOC G/L	464
VOC Lbs./Gal.	3.87
Flammable	Yes
Plastic Safe	Yes
Average Dry Time	15 to 30 Minutes
Coverage	20 to 25 Square Feet
Dielectric Strength	2,000 Volts/Mil
Working Temp [Degrees F]	-90 to 250°F
Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Consumer Commodity, ORM-D
VOC Compliant for CA & OTC	Not Regulated
Removal (How To)	DRY paint with lacquer thinner/stripper., Remove: WET paint with mineral spirits or turpentine

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)