

型號

CT-DHC3J6NL

名稱

超小型電子計數器 Counter

產品外觀



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

- DIN48X24mm標準面板尺寸,可擴展成50x60mm
- 內部自帶電源,不需外接,內置鋰電池壽命 ≥ 10 年
- 可輸入接點信號,或電信號,計數準確可靠
- LCD顯示,顯示大而清晰
- 最高計數速度200CPS
- 無機械磨損,壽命長
- 電源:內部電源
- 電池壽命: ≥ 10 年
- 計數範圍:0~999999
- 顯示字高:6.7mm
- 復歸方式:接點
- 接點接通最大電阻 $\leq 10K\Omega$ (計數ON)
- 接點斷開最小電阻 $\geq 500K\Omega$ (計數OFF)
- 輸入最大殘餘電壓0.5V
- 輸入信號電壓: L:0~2V H:4~30V
- 輸入阻抗: $\geq 4.7K$
- 復歸最小脈寬: ≥ 0.2 秒
- 重量:約60g
- 開孔尺寸:22.2X45mm
- 計數器的信號輸入,及復歸輸入的開關或電路應儘量靠近計數器的接線端子
- 復歸信號不應長時間接通,以免浪費內部電池
- 接點輸入應可靠,以免接點回跳引起錯誤計數

- DIN 48x24mm Standard Faceplate Area, can expand to 50X60mm
- Internal power source, no need for external power
- Can use ON/OFF signal or communications signal, counter is reliable
- LED display, large and clear.
- Maximum timer speed of 200 CPS
- No mechanical wear out, long lifetime
- Battery Life-Expectancy: ≥ 10 Years
- Counter Range: 0-999999
- Number Display Height: 6.7mm
- Rest Method: ON/OFF
- ON/OFF maximum resistance $\leq 10K\Omega$ (Counter ON)
- ON/OFF minimum resistance $\geq 500K\Omega$ (Counter OFF)
- Maximum Residual Voltage 0.5V
- Input Signal: L:0-2V H:4-30V
- Input Resistance: $\geq 4.7K$
- Minimum Reset Delay: ≥ 0.2 seconds
- Weight: Approximately 60g
- Dimension of Mounting Hole: 22.2X45mm
- Counter Signal Input, and reset on/off or switch should be as close as possible to the wired end of the counter.
- Avoid mangling wires.
- Reset signal should not be applied for a long time so that internal battery will not be wasted.
- ON/OFF input should be reliable to prevent a reset that will cause incorrect results.

