

Model # DE-2001 / DE-2002 / DE-2003 



- **Auto Hold !!!**
- Auto power off **selection**
- **Auto range** & manual range
- **Capacitance measurement** (DE-2001)
- Rubber holster protection & stand rack
- Dual Insulation test leads
- Warning beep emit exceed 11A test (DE-2001)

Size : 155 (L) x 74 (W) x 31 (H) mm
Weight : 240g

■ **CE approval:** EN61010-1, EN61010-2 (Pollution degree 2, EN-61326-01)

Specifications:

- **ACV (0.001V ~ 600V)** : 4V / 40V / 400V / 600V
- **DCV (0.1mV ~ 600V)** : 400mV / 4V / 40V / 400V / 600V
- **DCA (0.1uA ~ 20A)** : 400uA / 4000uA / 40mA / 400mA / 10A (max. 20A)
- **ACA (0.1uA ~ 20A)** : 400uA / 4000uA / 40mA / 400mA / 10A (max. 20A)
- **Ω (0.1Ω ~ 40MΩ)** : 400Ω / 4KΩ / 40KΩ / 400KΩ / 4MΩ / 40MΩ
- **Capacitor (0.01nF ~ 200uF)** : 20nF / 200nF / 2uF / 20uF / 200uF
- **Continuity check** : Yes
- **Diode test** : Yes
- **Overload indicator** : OL & **Beep**
- **Low battery indicator** : Yes
- **LCD Display** : 3 3/4 digit 4300 counts
- **Sampling rate** : 2 times/sec.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)