



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Material:

Housing: 30% Glass filled PBT or PPS UL94V-0.

Contacts: Phosphor Bronze.

Plating: Tin plated.

Electrical Characteristics:

Current Rating: 1 AMP.

Insulator Resistance: 5000M Ω min. at DC 500V.

Contact Resistance: 20m Ω max. at DC 100mA.

Operating Temperature: -55°C ~ +105°C.

Capacitance: 1.0pF max between adjacent contacts.

Features:

- Through hole.
- Accept chip carriers conforming to JEDEC spec.
- High temp PPS insulator available.

Product No.	Dimension				
	A	B	C	D	E
C20-20P	15.50	15.50	16.70	5.08	5.08
C20-28P	18.00	18.00	20.38	7.62	7.62
C20-32P	18.00	20.58	22.34	7.62	10.16
C20-44P	23.58	23.58	27.60	12.70	12.70
C20-52P	25.90	25.90	31.40	15.24	15.24
C20-68P	PBT	31.80	31.80	40.15	20.32
	PPS	31.10	31.10	38.40	20.32
C20-84P	PBT	36.70	36.70	47.20	25.40
	PPS	36.00	36.00	45.60	25.40

