

DS26LS32C/DS26LS32M/DS26LS32AC/DS26LS33C/ DS26LS33M/DS26LS33AC Quad Differential Line Receivers

General Description

The DS26LS32 and DS26LS32A are quad differential line receivers designed to meet the RS-422, RS-423 and Federal Standards 1020 and 1030 for balanced and unbalanced digital data transmission.

The DS26LS32 and DS26LS32A have an input sensitivity of 200 mV over the input voltage range of $\pm 7V$ and the DS26LS33 and DS26LS33A have an input sensitivity of 500 mV over the input voltage range of $\pm 15V$.


Both the DS26LS32A and DS26LS33A differ in function from the popular DS26LS32 and DS26LS33 in that input pull-up and pull-down resistors are included which prevent output oscillation on unused channels.

Each version provides an enable and disable function common to all four receivers and features TRI-STATE® outputs with 8 mA sink capability. Constructed using low power Schottky processing, these devices are available over the full military and commercial operating temperature ranges.


Features

- High differential or common-mode input voltage ranges of $\pm 7V$ on the DS26LS32 and DS26LS32A and $\pm 15V$ on the DS26LS33 and DS26LS33A
- $\pm 0.2V$ sensitivity over the input voltage range on the DS26LS32 and DS26LS32A, $\pm 0.5V$ sensitivity on the DS26LS33 and DS26LS33A
- DS26LS32 and DS26LS32A meet all requirements of RS-422 and RS-423
- 6k minimum input impedance
- 100 mV input hysteresis on the DS26LS32 and DS26LS32A, 200 mV on the DS26LS33 and DS26LS33A
- Operation from a single 5V supply
- TRI-STATE outputs, with choice of complementary output enables for receiving directly onto a data bus

Logic Diagram



Connection Diagram



Top View

Order Number DS26LS32CM, DS26LS32CN,
 DS26LS32ACM, DS26LS32ACN, DS26LS33ACM
 or DS26LS33ACN


See NS Package Number M16A or N16E

For Complete Military Product Specifications,
 refer to the appropriate SMD or MDS.

Order Number DS26LS32MJ/883, DS26LS32MW/883,
 DS26LS32ME/883, DS26LS33MW/883

See NS Package Number E20A, J16A or W16A

20-Lead Ceramic Leadless Chip Carrier



Truth Table

ENABLE	ENABLĒ	Input	Output
0	1	X	Hi-Z
See Note Below		V _{ID} ≥ V _{TH} (Max)	1
		V _{ID} ≤ V _{TH} (Min)	0

Hi-Z = TRI-STATE®

Note: Input conditions may be any combination not defined for ENABLE and ENABLĒ.

Absolute Maximum Ratings (Note 3)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage	7V
Common-Mode Range	$\pm 25V$
Differential Input Voltage	$\pm 25V$
Enable Voltage	7V
Output Sink Current	50 mA
Maximum Power Dissipation (Note 1) at 25°C	
Cavity Package	1433 mW
Molded Dip Package	1362 mW
SO Package DS26LS32	1002 mW
DS26LS32A	1051 mW
Storage Temperature Range	-65°C to +165°C
Lead Temperature (Soldering, 4 seconds)	260°C

Operating Conditions

		Min	Max	Units
Supply Voltage, (V_{CC})				
DS26LS32M, DS26LS33M (MIL)	4.5	5.5	V	
DS26LS32C, DS26LS33C	4.75	5.25	V	
DS26LS32AC, DS26LS33AC (COML)				
Temperature, (T_A)				
DS26LS32M, DS26LS33M (MIL)	-55	+125	°C	
DS26LS32C, DS26LS33C	0	+70	°C	
DS26LS32AC, DS26LS33AC (COML)				
Note 1: Derate cavity package 9.6 mW/°C above 25°C; derate molded DIP package 10.9 mW/°C above 25°C.				
Note 2: Derate SO Package 8.01 mW/°C for DS26LS32				
	8.41 mW/°C for DS26LS32A			

Electrical Characteristics (Notes 4, 5, 6)

over the operating temperature range unless otherwise specified

Symbol	Parameter	Conditions		Min	Typ	Max	Units
V_{TH}	Differential Input Voltage	$V_{OUT} = V_{OH}$ or V_{OL}	$DS26LS32, DS26LS32A, -7V \leq V_{CM} \leq +7V$	-0.2	± 0.07	0.2	V
			$DS26LS33, DS26LS33A, -15V \leq V_{CM} +15V$	-0.5	± 0.14	0.5	V
R_{IN}	Input Resistance	$-15V \leq V_{CM} \leq +15V$ (One Input AC GND)		6.0	8.5		kΩ
I_{IN}	Input Current (Under Test)	$V_{IN} = 15V$, Other Input $-15V \leq V_{IN} \leq +15V$				2.3	mA
		$V_{IN} = -15V$, Other Input $-15V \leq V_{IN} \leq +15V$				-2.8	mA
V_{OH}	Output High Voltage	$V_{CC} = \text{MIN}, \Delta V_{IN} = 1V, V_{ENABLE} = 0.8V, I_{OH} = -440 \mu A$		Commercial	2.7	4.2	V
		Military		2.5	4.2		V
V_{OL}	Output Low Voltage	$V_{CC} = \text{Min}, \Delta V_{IN} = -1V, V_{ENABLE} = 0.8V$		$I_{OL} = 4 \text{ mA}$		0.4	V
		$V_{CC} = \text{Min}, \Delta V_{IN} = -1V, V_{ENABLE} = 0.8V$		$I_{OL} = 8 \text{ mA}$		0.45	V
V_{IL}	Enable Low Voltage					0.8	V
V_{IH}	Enable High Voltage			2.0			V
V_I	Enable Clamp Voltage	$V_{CC} = \text{Min}, I_{IN} = -18 \text{ mA}$				-1.5	V
I_O	OFF-State (High Impedance) Output Current	$V_{CC} = \text{Max}$		$V_O = 2.4V$		20	μA
				$V_O = 0.4V$		-20	μA
I_{IL}	Enable Low Current	$V_{IN} = 0.4V$				-0.36	mA
I_{IH}	Enable High Current	$V_{IN} = 2.7V$				20	μA
I_{SC}	Output Short-Circuit Current	$V_O = 0V, V_{CC} = \text{Max}, \Delta V_{IN} = 1V$		-15		-85	mA
I_{CC}	Power Supply Current	$V_{CC} = \text{Max}, \text{All } V_{IN} = \text{GND}, \text{ Outputs Disabled}$		DS26LS32, DS26LS32A	52	70	mA
				DS26LS33, DS26LS33A	57	80	mA
I_I	Input High Current	$V_{IN} = 5.5V$				100	μA
V_{HYST}	Input Hysteresis	$T_A = 25^\circ C, V_{CC} = 5V, V_{CM} = 0V$		DS26LS32, DS26LS32A	100		mV
				DS26LS33, DS26LS33A	200		mV

Note 3: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the device should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 4: All currents into device pins are shown as positive, all currents out of device pins are shown as negative, all voltages are referenced to ground, unless otherwise specified. All values shown as max or min are so classified on absolute value basis.

Note 5: All typical values are $V_{CC} = 5V, T_A = 25^\circ C$.

Note 6: Only one output at a time should be shorted.


Switching Characteristics

$V_{CC} = 5V$, $T_A = 25^\circ C$


Symbol	Parameter	Conditions	DS26LS32/DS26LS33			DS26LS32A/DS26LS33A			Units
			Min	Typ	Max	Min	Typ	Max	
t_{PLH}	Input to Output	$C_L = 15 \text{ pF}$		17	25		23	35	ns
t_{PHL}				17	25		23	35	ns
t_{tL}	ENABLE to Output	$C_L = 5 \text{ pF}$		20	30		15	30	ns
t_{tH}				15	22		20	25	ns
t_{zL}	ENABLE to Output	$C_L = 15 \text{ pF}$		15	22		14	22	ns
t_{zH}				15	22		15	22	ns

AC Test Circuit and Switching Time Waveforms


Load Test Circuit for TRI-STATE® Outputs



Propagation Delay (Notes 7, 9)



Enable and Disable Times (Notes 8, 9)




Note 7: Diagram shown for ENABLE low.

Note 8: S1 and S2 of load circuit are closed except where shown.

Note 9: Pulse generator for all pulses: Rate = 1.0 MHz; $Z_O = 50\Omega$; $t_f \leq 6 \text{ ns}$; $t_r \leq 6.0 \text{ ns}$.

Typical Applications


Two-Wire Balanced Interface—RS-422




勝特力材料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Typical Applications (Continued)



Single Wire with Driver Ground Reference—RS-423



Physical Dimensions inches (millimeters) unless otherwise noted





Ceramic Dual-In-Line Package (J)
 Order Number DS26LS32MJ/883 or DS26LS33MJ/883
 NS Package Number J16A




Small Outline Package (M)
 Order Number DS26LS32CM, DS26LS32ACM, or DS26LS33ACM
 NS Package Number M16A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



DS26LS32C/DS26LS32M/DS26LS32C/DS26LS33C/DS26LS33M/DS26LS33AC Quad Differential Line Receivers

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



20 Lead Ceramic Leadless Chip Carrier (E)
 Order Number DS26LS32ME/883
 NS Package Number E20A

E20A (REV D)

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

