



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

REV	MODIFICATION	DATE	DRAW

NOTES:

SPECIFICATION:

- 1.Current Rating: 3 A
- 2.Withstanding Voltage: 1000 VAC (1 Minute)
- 3.Insulation Resistance: 5000 Megohms Min.
- 4.Contact Resistance: 25 Milliohms Max.
- 5.Operating Temperature: -55°C to +105°

MATERIAL:

- 1.Contact: Brass
- 2.Insulator:P.B.T. + 30%(UL94V-0)
- 3.Shell:Steel

ORDER INFORMATION

DSBRH-M1501B406

DIMENSION IN mm [Inch]		PROD. SPEC.	KINGFONT PRECISION INDUSTRIAL CO., LTD.
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	
.X±0.30	X.*±	APPROVE	FILE NO. _____ DWG NO. DSBRH-M1501B406
.XX±0.20	.X.*±	CHECK	
.XXX±0.10	.XX.*±	DRAW	SIZE A4 SCALE 2:1 REV A