

Productinfo

DOUBLE-FIX mounting tape

Product description

Double-sided, self-adhesive mounting tape.



Field of application

Adheres photographs, posters, wallhooks, name plates, mirrors, calendars, plastic containers, soap dishes, and pictures to any flat and smooth surface such as ceramic tiles, glass, metal, wood, plastics, painted surfaces, formica and hardboard. Not suitable for heavy and protruding objects, rough, irregular or dusty surfaces (brick, plaster). Do not apply the product to vinyl wallcovering.

Properties

- Temp. resistance: - 20°C up to + 70°C.
- Frost resistance: good.
- Resistance to chemicals: moderate.
- Ageing resistance: good.

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)

PORCELAIN REPAIR

PRODUCT DESCRIPTION

Thick liquid repair adhesive, based on nitro-synthetic resins.

FIELD OF APPLICATION

For bonding porcelain, marble, crockery, ceramics and ivory. Can be used as an adhesive as well as a sealant.

PROPERTIES

Dilutability: dilute with acetone.

Temp. resistance: from -30°C up to $+80^{\circ}\text{C}$.

Resistance to moisture: resistant to hot water.

Resistance to chemicals: resistant to mineral oils, diluted acids and cleaning products.

TECHNICAL DATA

| | |
|------------------|---------------------------|
| Basic material | : nitro-synthetic resins |
| Colour | : white. |
| Curing time | : 24 hours. |
| Solids content | : 52%. |
| Specific gravity | : 0.95 g/ml. |
| Flash point | : $+21^{\circ}\text{C}$. |

APPLICATION

Surface treatment: The materials to be bonded should be dry, clean and free from rust and grease.

Tools: Can be applied directly from the tube.

Directions for use: Apply a thin layer of adhesive to both surfaces and allow to dry. Then apply again a layer of adhesive to just one part and press both parts together. Allow to dry for 24 hours. Wash the item thoroughly before use.


STAINS

Remove adhesive stains with acetone.

STORAGE PROPERTIES

Bison Porcelain Repair has a shelf life of about 8 months, provided it is stored in unopened packing in a cool, dry place, in well-closed packing.

WARNING

| | | |
|--------|---|---|
| Symbol | = F. |  |
| S2 | = Keep out of reach of children. | |
| S16 | = Keep away from sources of ignition | |
| | No smoking | |
| S46 | = If swallowed, seek medical advice immediately and show this container or label. | |
| S51 | = Use only in well ventilated areas | |

TRANSPORT CLASSIFICATIONS

On land: RID/ADR = 3 - 5 C

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Our instructions are based on extensive investigations and experience. In view of the large variety of materials and the conditions under which our products are applied, no responsibility can be assumed for the results obtained and/or any damage caused from the use of the product. However, our Service Department is quite willing to supply any advice needed.

Head office: Bison International - P.O. Box 160, 4460 AD Goes (NL). Tel. 31-113-248248, Fax 31-113-232077, e-mail: info@bison.boltongroup.nl