



Note:

1.Material:

- 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: Copper alloy,t=0.25mm
- 1.3 Shell: Spcc,t=0.40mm,50P Front-shell t=0.60mm

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min.
- 2.5 Total mating force: 9.0 Kgf Max.
- 2.6 Total unmating force: 5.0 Kgf Min.
- 2.7 Temperature range: -55°C~85°C

PART NO.	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2
C-14S	43.92	35.99	25.2	12.25	11.9
C-24S	54.71	46.79	36.0	12.25	11.9
C-36S	67.69	59.74	48.9	12.25	11.9
C-50S	82.78	74.85	64.0	12.25	11.9

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

				DRAWN:	GENERAL TOLERANCE:		
E				CHECKED:	UNIT:	DESCRIPTION: E24-xxP	SIZE A4
D					SCALE:		
C					SHEET:		
B		JECSON			PROJECTION:		
A							