



# CONQUER

## ELECTRONICS FUSES

### EAJ Quick Acting Low Breaking Capacity



. 5 $\phi$  x 20 mm ( 0.197 x 0.787 inch )  
Ampere Rating: 50mA to 20 A  
Voltage Rating: 60V and less

#### Electrical Characteristics:

In	1.5 In	2.1 In	4 In	10 In
	Min.	Max.	Max.	Max.
50mA - 20A	60 min	30 min.	300ms	20ms

### AUE Normal Blow Glass Tube Fuses



. 10.3 $\phi$  x 38.1 mm ( 13/32 x 1-1/2 inch )  
Ampere Rating: 500mA to 80A  
Voltage Rating: 250V and less

#### Electrical Characteristics :

135% - 1 Hour, **Maximum**  
200% - 30 Seconds, **Maximum**  
Caps: Gold Finish For High Performance

#### Approvals:



30A and less  
Replaces AGU and 5AG Fuses

### JUE Normal Blow Glass Tube Fuses



. 10.3 $\phi$  x 38.1 mm ( 13/32 x 1-1/2 inch )  
Ampere Rating: 500mA to 60A  
Voltage Rating: 250V and less

#### Electrical Characteristics :

160% - 1 Hour, **Maximum**  
200% - 120 Seconds, **Maximum**  
Caps: Gold Finish For High Performance

#### Approvals:



1A to 30A and less

**Option** : Ceramic Tube Also Available

Model No: **JUB**

### AUB Fast Acting Ceramic Tube Fuses



. 10.3 $\phi$  x 38.1 mm ( 13/32 x 1-1/2 inch )  
Ampere Rating: 500mA to 80A  
Voltage Rating: 600V and less

#### Electrical Characteristics :

135% - 1 Hour, **Maximum**  
200% - 120 Seconds, **Maximum**  
Caps: Gold Finish For High Performance

**Standards:** UL Listed ,CSA Certified  
30A and less

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)