

## MAIN SPECIFICATIONS

**Insulator material:NYLON 66(UL 94V-O)**

**Wire range:AWG#28~#22**

**Rated voltage:250V**

**Rated current:1A**

**Contact resistance: 0.01**

**Insulation resistance: 1000M**

**Withstanding voltage:1000V.AC**

**Temp range for usage:-25~85**

**Relative humidity:93%+40 °**

**P.C board thickness:1.6mm**

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



### Terminal

Wier Range		O.D of Wire ins	Q' ty/reel
mm <sup>2</sup>	AWG#	mm	
0.06~0.33	28~22	1.2~1.9	7000PCS

### Housing

Position	Dimension	
	A	B
2	2.54	5.74
3	5.80	8.28
4	7.62	10.82
5	10.16	13.36
6	12.70	15.90
7	15.24	18.44
8	17.78	20.98
9	20.32	23.52
10	22.86	26.06
11	25.40	28.60
12	27.94	31.14
13	30.48	33.68
14	33.02	36.22
15	35.56	38.76
16	38.10	41.30
17	40.64	43.84
18	43.18	46.38
19	45.72	48.92
20	48.26	51.46

### Wafer

Position	Dimension	
	A	B
2	2.54	5.08
3	5.80	7.62
4	7.62	10.16
5	10.16	12.70
6	12.70	15.24
7	15.24	17.78
8	17.78	20.32
9	20.32	22.86
10	22.86	25.40
11	25.40	27.94
12	27.94	30.48
13	30.48	33.02
14	33.02	35.56
15	35.56	38.10
16	38.10	40.64
17	40.64	43.18
18	43.18	45.72
19	45.72	48.26
20	48.26	50.80