

FEATURE

- Compact size , light weight
- Over load protection
- DC output plug option
- Short circuit protection
- Low cost / high reliability
- 100% full load burn-in test
- 1 year warranty



ELECTRICAL SPECIFICATIONS

Input

Input range ----- 90 – 240VAC(Full Range) , 47 – 63Hz
Input current (rms) --- 160mA @ 90VAC; 80mA @ 264VAC MAX
Efficiency ----- >80% @ full load, 115VAC (DC Conversion)

Output

Voltage (Vo) ----- +5V ~ +12V
Voltage regulation --- ±8% @ constant voltage mode
Current limit ----- ±8% @ constant current mode
Maximum power (Po) ----- 5W
Setup , hold-up time----- 800ms , 8ms @ full load and 115VAC
Protection ----- Over voltage protection (OVP),AC recycle
Short circuit protection; Output short circuit protection (<0.03 ohm)
Pulsing mode , auto recovery
Length of output cable ----- 180 cm , AWG 22 X 2C
Standard plug of DC output ----- As your instruction 
Inrush current ----- cold start , < 5A peak @ 115VAC
Withstand voltage ---- I/P – O/ P : 3.0 KVAC , 1min

SAFETY

FCC ----- part 15 , class B
CE ----- EMI ----- EN 55022 , class B
EN 61000-3-2
CE 61000-3-3
EMS ----- EN 55024

ENVIRONMENTAL

Operating temperature ----- 0 °C to +40 °C ambient
Storage temperature ----- -10 °C to +70 °C
Humidity ----- 20% ~ 90% RH

勝特力材料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

ORDERING INFORMATION

Model	Output Rating	Tol.	R&N	Pmax.
FA033-1000	3.3V/1.00A ±50mA	8%	50mV	3W
FA450-1000	4.5V/1.00A	8%	50mV	4.5W
FA050-1000	5V/1.00A	8%	60mV	5W
FA060- 900	6V/0.90A	8%	90mV	5W
FA120- 500	12V/0.5A	8%	120mV	5W

其他特殊規格可訂製，最低量500 pcs