



Optical (With Dichroic Reflector)

image

GZ4 Base(MR11)

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Focal Distande (mm)	Beam Angle (°)	Color Temp (K)	Avg Life (H)	Fig.No.
				Ref Dia (A)	MOL (B)					
EDR/M 6V 10W/H20		6	10	35.8	36.0	3800	27	2800	2000	1
*EDR/M 6V 15W/AL		6	15	35.8	33.3	1800	-	3200	50	4
EDR/M 7.2V 15W		7.2	15	35.8	33.3	800	-	3200	50	4
EDR/M 6V 20W		6	20	35.8	33.3	5900	-	3200	50	4
EDR/M 6V 20W/F		6	20	35.8	33.3	3200	-	3200	50	4
EDR/M 7.2V 20W/F		7.2	20	35.8	33.3	1500	-	3200	50	4
EDR/M 9.6V 20W		9.6	20	35.8	33.3	500	-	3200	50	4
EDR/M 9.6V 20W/F		9.6	20	35.8	33.3	900	-	3200	50	4
EDR/M 12V 20W		12	20	35.8	33.3	33.3	-	3200	50	4
EDR/M 12V 20W/F		12	20	35.8	33.3	33.3	-	3200	50	4
EDR/M 12V20W/H20		12	20	35.8	38.0	38.0	27	2950	2000	2
FLT 13.8V25W/S	FLT	13.8	25	35.3	35.0	35.0	120	3100	500	3
EDR/M 12V 28W		12	28	35.8	35.0	35.0	216	3000	300	2
EDR/M 12V 30W		12	30	35.8	33.3	33.3	-	3200	50	4
EDR/M 9.5V 50W/D		9.5	50	35.0	36.0	36.0	26.5	-	25	2
EDR/M 12V50W		12	50	35.8	35.0	35.0	29.5	50	2	2
EDR/M 12V 75W/D		12	75	35.0	36.0	36.0	26.5	50	2	2

*Aluminized Coating

G5.3-4.8 Base

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Focal Distande (mm)	Color Temp (K)	Avg Life (H)	Fig.No.
				Ref Dia (A)	MOL (B)				
EDR/M12V 50W/SD		12	50	35.0	37.0	26.5	-	25	5
EDR/M12V 75W/SD		12	75	35.0	37.0	26.5	-	50	5
EDR/M12V 100W/SD		12	100	35.0	37.0	26.5	-	25	5

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Focal Distande(mm)	Color Temp (K)	Avg Life (H)	Fig.No.
				Ref Dia (A)	MOL (B)				
EZE 82V 150W		82	150	42.0	44.5	152.4	3250	150	6
EXY 82V 250W		82	250	42.0	44.5	152.4	3250	250	6
EXR 82V 300W		82	300	42.0	44.5	152.4	3350	35	6
EXW 82V 300W		82	300	42.0	44.5	152.4	3400	15	6
FHS 82V 300W		82	300	42.0	44.5	152.4	3300	70	6

GX5.3 Base(MR16)

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Focal Distande (mm)	Color Temp (K)	Avg Life (H)	Filament	Fig. No.
				Ref Dia (A)	MOL (B)					
FHX 13.8V 25W	FHX	13.8	25	50.7	44.5	108	3100	250	CC-6	7
EDR 13.8V 25W		13.8	25	50.7	44.5	108	3150	500	CC-6	7
EKZ 108.8V 30W	EKZ	10.8	30	50.7	44.5	38.1	3100	200	CC-6	7
FJX 13.8V 30W	FJX	13.8	30	50.7	44.5	108	3150	500	CC-6	7
EPN 12V 35W	EPN	12	35	50.7	44.5	29	3300	50	C-6	7
EPT 10.8V 42W	EPT	10.8	42	50.7	44.5	38.1	2900	8000	CC-6	7
JR 12V 50W/G/M		12	50	50.7	44.5	38.1	3000	2000	C-8	7
DJT 13.8V 50W	DJT	13.8	50	50.7	44.5	152	3150	1000	CC-6	7
EPZ 13.8V 50W	EPZ	13.8	50	50.7	44.5	108	3150	1000	CC-6	7
ENZ 30V 50W	ENZ	30	50	50.7	44.5	29	3400	25	CC-6	7

DDK 19V 80W	DDK	19	80	50.7	44.5	152.4	3300	40	CC-6	7
DDM 19V 80W	DDM	19	80	50.7	44.5	152.4	3350	50	CC-6	7
EJY 19V 80W	EJY	19	80	50.7	44.5	38.1	3400	25	CC-6	7
EKG 19V 80W	EKG	19	80	50.7	44.5	44.5	3400	25	CC-6	7
ENW 19V 80W	ENW	19	80	50.7	44.5	44.5	3200	200	C-8	7
DDS 21V 80W	DDS	21	80	50.7	44.5	165	3125	500	CC-6	7
EKP/ENA 30V 80W	EPK/ ENA	30	80	50.7	44.5	44.5	3400	25	CC-6	7
ELB 30V 80W	ELB	30	80	50.7	44.5	29	3400	15	CC-6	7
DED13.8V 85W	DED	13.8	85	50.7	44.5	165.0	3150	1000	CC-6	7
EPX 14.5V 90W	EPX	14.5	90	50.7	44.5	165.1	3150	500	CC-6	7
EPV 14.5V 90W	EPV	14.5	90	50.7	44.5	155.2	3150	500	CC-6	7
EMC 12V 100W	EMC	12	100	50.7	44.5	142	3200	200	CC-6	7
EDR 20V 150W/ H5	EDR	12	100	50.7	44.5	180	3150	2000	CC-6	7
EKN 17.7V 120W	EKN	17.7	120	50.7	44.5	38.1	3200	120	CC-6	7
DDL 20V 150W	DDL	20	150	50.7	44.5	194.5	3150	500	CC-6	7
EDR 20V 150W/ H5		20	150	50.7	44.5	194.5	3150	500	CC-6	7
EJA 21V 150W	EJA	21	150	50.7	44.5	28	3400	40	CC-6	7
EJM 21V 150W	EJM	21	150	50.7	44.5	38.1	3400	40	CC-6	7
EJN 21V 150W	EJN	21	150	50.7	44.5	50.8	3400	40	CC-6	7
EKE 21V 150W	EKE	21	150	50.7	44.5	44.5	3250	200	CC-6	7
EJV 21V 150W	EJV	21	150	50.7	44.5	44.5	3400	40	CC-6	7
ELD 21V 150W	ELD	21	150	50.7	44.5	165.0	3400	40	CC-6	7
JER 100V 150W		110	150	50.7	44.5	31.7	-	50	CC-8	7
EJL 24V 200W	EJL	24	200	50.7	44.5	31.7	3400	50	CC-6	7
EKX 24V 200W	EKX	24	200	50.7	44.5	139.7	3400	25	CC-6	7
EWf 24V 200W	EWf	24	200	50.7	44.5	298.5	3350	50	CC-6	7
ELC 24V 250W	WLC	24	250	50.7	44.5	31.7	3400	50	CC-6	7
ERV 36V 340W	ERV	36	340	50.7	44.5	298.5	3300	75	CC-8	7

GY5.3 Base(MR16)

胜特力材料 886-3-5753170
 胜特力电子(上海) 86-21-54151736
 胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Focal Distande (mm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				Ref Dia (A)	MOL (B)					
ESH 82V 85W	ESH	82	85	50.7	44.5	152.0	-	250	CC-8	8
JER 82V 85W	ESJ	82	85	50.7	44.5	32.0	-	40	CC-8	8
ESD 12V 150W	ESD	120	150	50.7	44.5	44.5	-	12	CC-8	8
EDR 120V 150WB		120	150	50.7	44.5	-	3050	100	CC-8	8
JER 82V 200W		82	200	50.7	44.5	38.1	-	50	CC-8	8
EYA 82V 200W	EYA	82	200	50.7	44.5	38.1	3300	50	CC-8	8
EVW 82V 250W	EVW	82	250	50.7	44.5	298.5	3300	50	CC-8	8
EDR 100V 250W		100	250	50.7	44.5	298.5	3300	50	CC-8	8
ENH 120V 250W	ENH	120	250	50.7	44.5	152.4	3250	175	CC-8	8
ETJ 120V 250W	ETJ	120	250	50.7	44.5	36.5	3250	175	CC-8	8
EXX 120V 250W	EXX	120	250	50.7	44.5	-	3300	25	CC-8	8
ELH 100V 300W	ELH	100	300	50.7	44.5	152.4	3350	35	CC-8	8
EDR 100V 300W		100	300	50.7	44.5	31.7	3300	50	CC-8	8
EDR 100V 300W X		100	300	50.7	44.5	298.5	3200	50	CC-8	8
EDR 100V 300W X1		100	300	50.7	44.5	298.5	3200	50	CC-8	8
ELH 120V 300W	ELH	120	300	50.7	44.5	152.4	3350	35	CC-8	8
ENG 120V 300W	ENG	120	300	50.7	44.5	152.4	3450	15	CC-8	8
EWG 120V 300W	EWK	120	300	50.7	44.5	31.7	3400	35	CC-8	8
EYK 120V 300W	EYK	120	300	50.7	44.5	31.7	3300	60	CC-8	8
ENX 82V 360W	ENX	82	360	50.7	44.5	298.5	3300	75	CC-8	8
ENX-5 86V 360W	ENX-5	86	360	50.7	44.5	298.5	3300	75	CC-8	8
EPW 100V 360W	EPW	100	360	50.7	44.5	298.5	3300	75	CC-8	8
FXL 82V 410W	FXL	82	400	50.7	44.5	298.5	3300	75	CC-8	8

GZ6.35 Base(MR16)

胜特力材料 886-3-5753170

胜特力电子(上海) 86-21-54151736

胜特力电子(深圳) 86-755-83298787

Http://www.100y.com.tw

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension		Focal Distande (mm)	Color Temp (K)	Avg Life (H)	Filament	Fig.No.
				Ref Dia (A)	MOL (B)					
*EFM 8V 50W	EFM	8	50	50.0	42.0	32	3350	50	C-8	9
EFM/D 8V 50W	EFM	8	50	50.0	42.0	32	3350	50	C-8	9
EFN 12V 75W	EFN	12	75	50.0	42.0	32	3400	50	C-8	9
EFP 12V 100W	EFP	12	100	50.0	42.0	32	3400	50	C-8	9
EDR 12V 100W/H10		12	100	50.0	42.0	36	3100	1000	C-8	9
EDR 15V 150W/H5		15	150	50.0	42.0	36	3100	500	C-8	9
EFR 15V 150W	EFR	15	150	50.0	42.0	32	3400	50	C-8	9
EDR 15V 150W/M		15	150	50.0	42.0	32	4200	50	C-8	9
EDR 100V 150W		100	150	50.0	42.0	142	3050	25	CC-8	9

*Aluminized Coating

GX7.9 Base(44mm/57mm Dichroic Reflector)

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Focal Distande (mm)	Color Temp (K)	Avg Life (H)	Fig.No.
				A	B	C				
ELS/ELR 16V 50W	ELS/ELR	16	50	44.5	40.6	15.9	205	3100	650	10
EPG 21V 80W	EPG	21	80	44.5	42.0	15.9	78.4	3300	100	10
EPF 30V 80W	EPF	30	80	44.5	40.6	15.9	78.4	3200	100	10
ELE 30V 80W	ELE	30	80	44.5	40.6	15.9	78.4	3400	20	10
ELZ 21V 150W	ELZ	21	150	57.2	45.1	15.9	69.1	3350	60	10
DNF 21V 150W	DNF	21	150	57.2	45.1	15.9	69.1	3400	25	10
ELV 21.5V 150W	ELV	21.5	150	57.2	45.1	15.9	69.1	3300	100	10
EMM 24V 250W	EMM	24	250	44.5	47.5	15.9	65.8	3400	25	10

G7.9 Base(44mm/57mm Dichroic Reflector)

Lamp Type	ANSI	Rated Voltages (V)	Power Consumption (W)	Outside Dimension			Focal Distande (mm)	Color Temp (K)	Avg Life (H)	Fig.No.
				A	B	C				
DNE 120V 150W	DNE	120	150	57.2	49.2	15.9	69.1	3350	12	11
BHB 120V 250W	BHB	120	250	44.5	47.5	15.9	65.8	3400	50	11