

POWER RELAY

1 POLE—10 A LOW PROFILE TYPE

FTR-H1 SERIES

RoHS compliant

■ FEATURES

- Working class: B (for IMQ)/ C (for VDE)
- Type of service: continuous duty
- Low profile (height 16.5 mm)/ cadmium free contacts
- 1 form A/ 1 form C 10 A, TV-5 rating available
- UL class B (130°C) insulation
- High isolation in small package (between coil and contacts)
 - Insulation distance : 8 mm
 - Dielectric strength : 5,000 VAC
 - Surge strength : 10,000 V
- Plastic materials —UL94 flame class V-0
UL CTI level class 2
- Plastic sealed relay
- Pin configuration compatible to VS/ FBR610 Series
- UL, CSA, BSI, VDE, SEMKO recognized
- Conforms to FIMKO, DEMKO
- Environmentally friendly cadmium free contacts type are available
- RoHS compliant since date code: 0434R
Please see page 7 for more information



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

■ ORDERING INFORMATION

[Example] FTR-H1 A A 005 V - **
 (a) (b) (c) (d) (e) (f)

(a)	Series Name	FTR-H1: FTR-H1 Series			
(b)	Contact Arrangement	A	: 1 form A (SPST-NO)		
		C	: 1 form C (SPDT)		
(c)	Coil Type	A	: Standard type (0.53 W)		
		D	: High sensitive type (0.4W)		
(d)	Nominal Voltage	005	: 5 VDC	012	: 12 VDC
		006	: 6 VDC	024	: 24 VDC
		009	: 9 VDC	048	: 48 VDC
(e)	Contact Material/TV Type	V	: Gold plate silver alloy (standard type)		
		T	: Gold plate silver alloy (TV-5 rating type, 1 form A standard type only)		
(f)	Custom Designation	Custom specification to be assigned			

Ordering Code Actual Marking
 FTR-H1AA005V H1AA005V

FTR-H1 SERIES

■ SAFETY STANDARD AND FILE NUMBERS

UL508, 873 (File No. E63614)

C22.2 No. 14 (File No. LR40304-30/LR107822)

VDE 0435, 0631, 0700, 0860 (File No. 11039-4940-1019)

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

	Nominal voltage	Contact rating
TV-Rating	5 ~ 48 VDC	TV-5 120 VAC 1/2 HP 250 VAC 1/3 HP 125 VAC 10 A 30 VDC/250 VAC resistive Pilot duty B 300, Q 300
General		1/2 HP 250 VAC 1/3 HP 125 VAC 10 A 30 VDC/250 VAC resistive 3A 250 VAC inductive (PF=0.4) Pilot duty B 300, Q 300

■ SPECIFICATIONS

Item			Standard Type	Sensitive	TV-5 Rating Type
Contact	Arrangement		1 form A (SPST-NO), 1 form C (SPDT)		1 form A (SPST-NO)
	Material		Gold plate silver alloy		
	Style		Single		
	Resistance (initial)		Maximum 100 m Ω (at 1 A 6 VDC)		
	Rating (Resistive)		10 A 250 VAC/30 VDC		
	Maximum Carrying Current		14 A		
	Maximum Switching Rating		2,500 VA/300 W		
	Maximum Switching Voltage		400 VAC 300 VDC		
	Maximum Switching Current		10 A		
	Minimum Switching Load*1		10 mA 5 VDC		
	Maximum Inrush Current		—		78 A 120 VAC (at lamp load)
Coil	Operating Range		80 to 110 % × V nominal		
	Nominal Power (at 20°C)		0.53 W	0.4W	0.53 W
	Operate Power (at 20°C)		0.26 W	0.225W	0.26W
	Operating Temperature		−40°C to +75°C (no frost) (refer to the CHARACTERISTIC DATA)		
Time Value	Operate (at nominal voltage)		Maximum 10 ms		
	Release (at nominal voltage)		Maximum 5 ms		
Insulation	Resistance (at 500 VDC)		Minimum 1,000 M Ω		
	Dielectric Strength	Between open contacts	1,000 VAC 1 minute		
		Between coil and contacts*2	5,000 VAC 1 minute		
	Surge Strength*3		10,000 V (at 1.2 x 50 μs)		
Life	Mechanical		2 × 10 ⁷ operations minimum		
	Electrical	Contact Rating	1 × 10 ⁵ operations minimum		
		Lamp Load	—		2.5 x 10 ⁴ ops. minimum
Other	Vibration Resistance	Misoperation	10 to 55 Hz (double amplitude of 1.65 mm)		
		Endurance	10 to 55 Hz (double amplitude of 3.3 mm)		
	Shock Resistance	Misoperation	100 m/s ² (11 ± ¹ ms)		
		Endurance	1,000 m/s ² (6 ± ¹ ms)		
	Weight		Approximately 12 g		

*1 Minimum switching loads mentioned above are reference values. Please perform the confirmation test with the actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

*2 IMQ

*3 IMQ

■ COIL DATA CHART

MODEL		Nominal Voltage	Coil Resistance (±10%)	Must Operate Voltage	Must Release Voltage
Standard Type	TV-5 Rating Type				
FTR-H1 (C, A) A005 V	FTR-H1AA005 T	5 VDC	47 Ω	3.5 VDC	0.5 VDC
FTR-H1 (C, A) A006 V	FTR-H1AA006 T	6 VDC	68 Ω	4.2 VDC	0.6 VDC
FTR-H1 (C, A) A009 V	FTR-H1AA009 T	9 VDC	155 Ω	6.3 VDC	0.9 VDC
FTR-H1 (C, A) A012 V	FTR-H1AA012 T	12 VDC	270 Ω	8.4 VDC	1.2 VDC
FTR-H1 (C, A) A024 V	FTR-H1AA024 T	24 VDC	1,100 Ω	16.8 VDC	2.4 VDC
FTR-H1 (C, A) A048 V	FTR-H1AA048 T	48 VDC	4,400 Ω	33.6 VDC	4.8 VDC

Note: All values in the table are measured at 20°C.


Sensitive Type

MODEL	Nominal Voltage	Coil Resistance (±10%)	Must Operate Voltage	Must Release Voltage
Standard Type				
FTR-H1 (C, A) D005 V	5 VDC	62 Ω	3.75 VDC	0.5 VDC
FTR-H1 (C, A) D006 V	6 VDC	90 Ω	4.5 VDC	0.6 VDC
FTR-H1 (C, A) D009V	9 VDC	202 Ω	6.75 VDC	0.9 VDC
FTR-H1 (C, A) D012 V	12 VDC	360 Ω	9.0 VDC	1.2 VDC
FTR-H1 (C, A) D024 V	24 VDC	1,440 Ω	18.0 VDC	2.4 VDC
FTR-H1 (C, A) D048 V	48 VDC	5,760 Ω	36.0 VDC	4.8 VDC


Note: All values in the table are measured at 20°C.

CHARACTERISTIC DATA


Timing




Timing




Coil temperature rise




Operating range




Operating range



Maximum Switching Power




Life Curve




REFERENCE DATA


Distribution of operate and release voltage




Distribution of operate and release time




Distribution of contact resistance




Mechanical life test



Electrical life test




Electrical life test




DIMENSIONS

● Dimensions


FTR-H1A type






● Schematics (BOTTOM VIEW)



● PC board mounting hole layout (BOTTOM VIEW)



FTR-H1C type



Unit: mm

RoHS Compliance and Lead Free Relay Information


1. General Information

- Relays produced after the specific date code that is indicated on each data sheet are lead-free now. Most of our signal and power relays are lead-free. Please refer to Lead-Free Status Info. (<http://www.fc.ai.fujitsu.com/pdf/LeadFreeLetter.pdf>)
 - Lead free solder paste currently used in relays is Sn-3.0Ag-0.5Cu. From February 2005 forward Sn-3.0Cu-Ni will be used for FTRB3 and FTR-B4 series relays.
 - Most signal and some power relays also comply with RoHS. Please refer to individual data sheets. Relays that are RoHS compliant do not contain the 6 hazardous materials that are restricted by RoHS directive (lead, mercury, cadmium, chromium IV, PBB, PBDE).
 - It has been verified that using lead-free relays in lead assembly process will not cause any problems (compatible).
 - "LF" is marked on each outer and inner carton. (No marking on individual relays).
 - To avoid lead relays (for lead-free sample, etc.) please consult with area sales office.
- We will ship lead relays as long as the lead relay inventory exists.

2. Recommended Lead Free Solder Profile

- Recommended solder paste Sn-3.0Ag-0.5Cu and Sn-3.0 Cu-Ni (only FTR-B3 and FTR-B4 from February 2005)

Reflow Solder condition



Flow Solder condition:

Pre-heating: maximum 120°C
Soldering: dip within 5 sec. at 260°C solder bath

Solder by Soldering Iron:

Soldering Iron
Temperature: maximum 360°C
Duration: maximum 3 sec.

We highly recommend that you confirm your actual solder conditions

3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays.

4. Tin Whisker

- SnAgCu solder is known as low risk of tin whisker. No considerable length whisker was found by our in-house test.

5. Solid State Relays

- Each lead terminal will be changed from solder plating to Sn plating and Nickel plating. A layer of Nickel plating is between the terminal and the Sn plating to avoid whisker.