

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**POLYCARBONATE MATERIAL:**  
**MOULDED IN:LIGHT GREY.**  
**OPERATING TEMPERATURE:-40C TO125C**  
**CLEAR LID IS AVAILABLE ON REQUEST.**

**HIGH IMPACT ABS MATERIAL:**  
**MOULDED IN : DARK GREY.**  
**OPERATING TEMPERATURE:-20C TO 100C**

- ✧ THE LID AND BASE INCORPORATE A TONGUE AND GROOVE SEALING SYSTEM WITH A NEOPRENE GASKET.
- ✧ WALL MOUNTING HOLES AND LID FIXING SCREWS ARE OUTSIDE THE SEATING AREA THUS PREVENTING THE INGRESS OF MOISTURE AND DUST.
- ✧ DESIGNED TO IP 65 OF IEC 529 AND NEMA 4(DUST AND HOSEPROOF).
- ✧ AVAILABLE WITH CLEAR OR LIGHT GRAY LIDS.
- ✧ INTERNAL GUIDE SLOTS FOR MOUNTING PCB ASSEMBLIES VERTICALLY.
- ✧ BOSSES ON INTERNAL BASE ALLOW FIXING OF PCB'S HORIZONTALLY OR CONNECTION OF TERMINALS,ETC INTO THREADED BRASS INSERTS.
- ✧ LID FIXING SCREWS ARE M-4 STAINLESS STEEL (NON-MAGNETIC) INTO THREADED BRASS INSERTS.
- ✧ THE POLYCARBONATE MATERIAL USED HAS A OPERATING TEMPERATURE OF -40 °C TO 100°C

MATERIAL		
POLYCARBONATE		
COLOR		
LIGHT GREY	POLYCARBONATE	
STOCK NO.	STOCK. CLEAR LID	EXTERNAL DIMENSIONS (MM)
	G238C	265 X 185 X 95
	G269C	200 X 120 X 80
	G2025C	240 X 160 X 120
G2038		300 X 230 X 111