



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## DB9F/DB25F Adapter Molded

### Key Features

- Whether you need to convert existing DB9 ports to DB25 or vice versa, this is an inexpensive alternative to buying new cables.

### Specification

#### • Details:

#### Connectors:

1x DB 9 Female

1x DB 25 Female

Type: D-Sub Adapter

#### Material:

Plug Material: Brass, Gold Flash

Contact Shell: Sheet metal, tin-plated

Insulator Material: Polyester resin. Glass and fiber reinforced.

Color: Beige jacket

Contact Material: N/A

Thumbscrews: 4-40 thread on both sides

#### Electrical:

Current Rating: 1 Amp


Dielectric Withstanding Voltage: AC 500V min. for 1 minute

Insulation Resistance: 1000M Ohms min. (@ 500V DC)


Contact Resistance: 15M Ohms max. mated

Working Temperature: -55 Deg. C to +105 Deg. C

### Technical Drawings / Photos



**DB9 Female**



**DB25 Female**

#### Pin Configuration:

DB9F	G	1	2	3	4
DB25F	G	8	3	2	20
DB9F		5	6	7	9
DB25F		7	6	4	22

### UL Information

- UL94V-0