



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

DB9M/DB25M Adapter Molded

Key Features

- Whether you need to convert existing DB9 ports to DB25 or vice versa, this is an inexpensive alternative to buying new cables.

Specification

• Details:

Connectors:

1x DB 9 Male
1x DB 25 Male

Type: D-Sub Adapter

Material:

Plug Material: Brass, Gold Flash

Contact Shell: Sheet metal, tin-plated

Insulator Material: Polyester resin. Glass and fiber reinforced.

Color: Beige jacket

Contact Material: N/A

Thumbscrews: 4-40 thread on both sides

Electrical:

Current Rating: 1 Amp

Dielectric Withstanding Voltage: AC 500V min. for 1 minute

Insulation Resistance: 1000M Ohms min. (@ 500V DC)

Contact Resistance: 15M Ohms max. mated


Working Temperature: -55 Deg. C to +105 Deg. C

Technical Drawings / Photos

DB9 Male



DB25 Male



Pin Configuration:

1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22
G	G

UL Information

- UL94V-0