

GDM-451

規格

DC VOLTAGE

Range 200mV, 2V, 20V, 200V, 1000V

Best Accuracy $\pm(0.05\%rdg + 3 \text{ digits})$

Input Impedance 10M Ω

AC VOLTAGE (40Hz ~ 400Hz)

Range 2V, 20V, 200V, 750V

Best Accuracy $\pm(0.5\%rdg + 10 \text{ digits})$

Input Impedance 2M Ω

DC CURRENT

Range 2mA, 20mA, 200mA, 20A

Best Accuracy $\pm(0.5\%rdg + 5 \text{ digits})$

AC CURRENT (50Hz ~ 400Hz)

Range 20mA, 200mA, 20A

Best Accuracy $\pm(0.8\%rdg + 10 \text{ digits})$

RESISTANCE

Range 200 Ω ~ 200M Ω 7 ranges

Best Accuracy $\pm(0.3\%rdg + 1 \text{ digit})$

CONTINUITY BEEPER

? Buzzer sounds if conductance less than 70 Ω

DIODE TEST

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Open Circuit Voltage approx. 2.8V typical

CAPACITANCE

Range 2nF, 20nF, 2μF, 20μF

Best Accuracy $\pm(3\%rdg + 40digits)$

FREQUENCY

Range 1Hz ~ 20kHz

Best Accuracy $\pm(1.5\%rdg + 5 digits)$

TEMPERATURE(°C)

Range -40°C ~ 1000°C

Best Accuracy $\pm 1\% + 30$

LCD DISPLAY

? 4 1/2 digits

POWER SOURCE

Single 9V battery (6F22)

ACCESSORIES

? Instruction manual

Battery

Test leads

DIMENSIONS &

80(W) x 165(H) x 38.3(D) mm

WEIGHT

Approx.275g

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Hand-Held Digital Multimeter

NEW



CE

GDM-451 (4 1/2 Digits)

FEATURES

- * 4 1/2 Digits 19999 counts
- * Manual Ranging
- * Continuity Check/Diode Test
- * Data Hold
- * Temperature Measurement
- * Capacitance, Frequency Measurement

NEW



CE

GDM-356 (3 1/2 Digits)

FEATURES

- * 3 1/2 Digits 1999 counts
- * Manual Ranging
- * Continuity Beeper/Diode Test
- * Capacitance Measurement
- * Frequency, Temperature Measurement

NEW



CE

GDM-350A (3 1/2 Digits)

FEATURES

- * 3 1/2 Digits 1999 counts
- * Manual Ranging
- * Continuity Beeper/Diode Test
- * Temperature Measurement

SELECTION GUIDE

Special Function	GDM-451	GDM-394	GDM-396	GDM-356	GDM-350A	GDM-395
Max. Display	19999	3999	3999	1999	1999	3999
Fused 10A Range		✓	✓			
Auto Ranging		✓	✓			✓
Diode	✓	✓	✓	✓	✓	✓
Continuity	✓	✓	✓	✓	✓	✓
Capacitance	✓	✓	✓	✓		✓
Frequency	20k	10M	10M	20k		100k
Temperature	✓		✓	✓	✓	
Duty Cycle(%)		✓	✓			✓
True RMS			✓			
Relative mode		✓	✓			✓
Data Hold	✓	✓	✓	✓	✓	✓
RS232C			✓			
Display Backlight	✓	✓	✓	✓	✓	

ORDERING INFORMATION

- GDM-451** 4 1/2 Digits Hand-Held DMM
- GDM-396** 3 3/4 Digits Hand-Held DMM with True R.M.S, Measurement and RS-232C Inter face
- GDM-394** 3 3/4 Digits Hand-Held DMM
- GDM-395** 3 3/4 Digits Hand-Held DMM
- GDM-356** 3 1/2 Digits Hand-Held DMM
- GDM-350A** 3 1/2 Digits Hand-Held DMM

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)