

# Specifications

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
 Http://www.100y.com.tw

## CYLINDRICAL TYPE



### Ultra Alkaline

Model No.	Dimension (mm)		Voltage (V)	Cross Reference			
	Diameter	Height		IEC	JIS	Energizer	Other
13AU	34.2	61.5	1.5	LR20	LR20	X95	D
14AU	26.2	50.0	1.5	LR14	LR14	X93	C
15AU	14.5	50.5	1.5	LR6	LR6	X91	AA
24AU	10.5	44.5	1.5	LR03	LR03	X92	AAA
908AU	66.0(L) x 66.0(W) x 111.0(H)		6.0	4LR25	4LR25X	529	-
1604AU	25.5(L) x 16.5(W) x 47.5(H)		9.0	6LR61	6LR61	X22	-

### Super Alkaline

Model No.	Dimension (mm)		Voltage (V)	Cross Reference			
	Diameter	Height		IEC	JIS	Energizer	Other
13A	34.2	61.5	1.5	LR20	LR20	E95	D
14A	26.2	50.0	1.5	LR14	LR14	E93	C
15A	14.5	50.5	1.5	LR6	LR6	E91	AA
24A	10.5	44.5	1.5	LR03	LR03	E92	AAA
25A	8.3	42.5	1.5	LR8D425	-	E96	AAAA
312A	62.0(L) x 22.0(W) x 67.0(H)		4.5	3LR12	-	-	-
908A	66.0(L) x 66.0(W) x 111.0(H)		6.0	4LR25	4LR25X	529	-
910A	12.0	30.2	1.5	LR1	LR1	E90	N
1604A	25.5(L) x 16.5(W) x 47.5(H)		9.0	6LR61	6LR61	522	-
1412AP	35.5(L) x 9.2(W) x 48.4(H)		6.0	4LR61	4LR61	539	J

### Digi 1 Nickel Zinc

Model No.	Dimension (mm)		Voltage (V)	Cross Reference			
	Diameter	Height		IEC	JIS	Eveready	Other
15NZ	14.5	50.5	1.5	-	-	-	AA

### Greencell Extra Heavy Duty

Model No.	Dimension (mm)		Voltage (V)	Cross Reference			
	Diameter	Height		IEC	JIS	Eveready	Other
13G	34.2	61.5	1.5	R20P	R20P	1250	D
14G	26.2	50.0	1.5	R14P	R14P	1235	C
15G	13.9	50.0	1.5	R6P	R6P	1215	AA
24G	10.5	44.5	1.5	R03	R03	1212	AAA
312G	62.0(L) x 22.0(W) x 67.0(H)		4.5	3R12	3R12	-	-
908G	66.0(L) x 66.0(W) x 111.0(H)		6.0	4R25	4R25	1209	-
918G	134.0(L) x 70.0(W) x 127.0(H)		6.0	4R25-2	4R25-2	-	-
1604G	26.5(L) x 17.5(W) x 48.5(H)		9.0	6F22	6F22	1222	-