

# OPERATION MANUAL FOR TEMP. & HUMIDITY METER

## 1. General Description:

This Temperature & Humidity Meter is characterized at:

- \* large-character LCD display
- \* multi-function
- \* low power consumption
- \* high stability & accuracy

## 2. Features:

- \* display temperature, humidity and time simultaneously
- \* memory of MAX & MIN measuring value
- \* 12-hour / 24-hour displaying system selectable
- \* °C/°F unit selectable
- \* integral-hour alarm function
- \* Alarm function
- \* Clock & Calendar function (month and date)
- \* Desk-top placing or Wall Hanging

## 3. specification:

### \* Temperature range:

\* temperature:  $-50 \sim +70^{\circ}\text{C}$  (  $-58 \sim +158^{\circ}\text{F}$  )

\* humidity range: 10%~99%RH

### \* resolution:

temperature:  $0.1^{\circ}\text{C}$  ( $0.1^{\circ}\text{F}$ )

humidity: 1% RH

### \* accuracy:

temperature:  $\pm 1^{\circ}\text{C}$  ( $1.8^{\circ}\text{F}$ )

humidity:  $\pm 5\% \text{RH}$  ( $40\% \sim 80\%$ )

\* power supply: 1.5V (AAA size) x 1

\* product dimension: 100 x 108 x 20 mm

\* weight: Approx. 160g

\* storage condition:  $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ , 20~80%RH

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)