


PRODUCT IDENTIFICATION



K5B

R6H

☐ **TS**



Material

Type

Turns

APPLICATIONS

- ◆ Computer products, mother board, TV card
- ◆ Power supplier, OA products, modem....
- ◆ Communications
- ◆ Countermeasures for complying with CE, FCC, VDE or VCCI radiated emissions
- ◆ Telecommunication equipments

FEATURES

- ◆ Compact, medium current high impedance EMI suppression component
- ◆ Wide Band Choke has been mainly used in PC products to filter EMI from the outside

DIMENSIONS (mm)

Core	A	B	C	D
R6H 6×10	6 ± 0.25	10 ± 0.30	0.9 ± 0.15	0.5 ± 0.05

Core	1.5 Ts	2 Ts	2.5 Ts
3 Ts	1.5 Ts×2	2.5 Ts (Π)	3 Ts (U)

PACKAGE

Bulk : 250 pcs / Per PE bag
1 Box : 6 PE bag (1,500pcs)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

■ SERIES LIST

No.	Part No.	Turns (Ts)	Min. 10MHz	Min. 50MHz	Min. 100MHz
1	K5B R6H 1.0Ts	1.0	58	148	178
2	K5B R6H 1.5Ts	1.5	155	290	335
3	K5B R6H 2.0Ts	2.0	200	450	480
4	K5B R6H 2.5Ts	2.5	295	615	580
5	A6 R6H 2.5Ts	2.5	385	660	580
6	K5B R6H 3.0Ts	3.0	355	790	550
7	K5B R6H 1.5Ts×2	1.5×2	155	290	335

Test frequency is 10MHz, 50MHz, 100MHz.

■ CHARACTERISTICS IMPEDANCE & FREQUENCY

