

7.5~10W AC-DC Wall Mount Universal/ Euro Type

- Universal AC input / Full range
- Two pole EURO plug in
- Class II power (without earth pin)
- Compact size , light weight
- Protections:short circuit/ over load/ over voltage/ over temp.
- Approvals:TUV/ CE
- Fix switching frequency and regulation
- 1 year warranty



AC input voltage.....90~264VAC
 AC inrush current.....cold start , < 60A peak @230VAC
 Over load protection.....hiccup mode , auto recovery
 Over voltage protection.....105%~145% of rated output voltage
 Set, hold up time.....300ms, 20ms at full load and 230VAC
 Withstand voltage.....I/P-O/P:3KVAC, 1minute
 Working temperature.....0~30°C @100%, 40°C @60% load
 Safety standards.....TUV EN60950 approved
 EMC standards.....EN55022 class B, EN61000-3-2,3,IEC801-2,3,4
 Length of output cable.....180cm of SPT-1, 20AWG× 2C
 Plug of DC output.....2.1 φ × 5.5 φ × 11mm, center “+”

Stock No.	Type No.	Output	Tol.	R&N	Eff.	P.P.
14221	KBM020-05M	5V, 1.5A	5%	50mV	70%	23
*14222	KBM020-09M	9V, 1.0A	5%	80mV	70%	23
14223	KBM020-12M	12V, 0.83A	3%	100mV	72%	23
*14224	KBM020-15M	15V, 0.67A	3%	100mV	72%	23
*14225	KBM020-24M	24V, 0.42A	3%	120mV	75%	23

*Min. order:200pcs/LOT(exclude first sample order)