



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Dual Darlington Transistor Module 150 Amperes/600 Volts



Description:
 The Powerex Dual Darlington Transistor Modules are high power devices designed for use in switching applications. The modules are isolated, consisting of two Darlington Transistors with each transistor having a reverse parallel connected high-speed diode.

- Features:**
- Isolated Mounting
 - Planar Chips
 - Discrete Fast Recovery Feedback Diode
 - High Gain (h_{FE})
 - Quick Connect Base-Emitter Signal Terminals
 - Base-Emitter Speed-up Diodes

- Applications:**
- AC Motor Control
 - DC Motor Control
 - Switching Power Supplies
 - Inverters

Ordering Information:
 Example: Select the complete eight digit module part number you desire from the table - i.e. KD324515 is a 450 $V_{CE0(sus)}$ (600 V_{CEV}), 150 Ampere Dual Darlington Module.

Outline Drawing

Dimensions	Inches	Millimeters
A	3.740 Max.	95 Max.
B	3.150 ± 0.01	80 ± 0.25
C	2.441 Max.	62 Max.
D	1.890 ± 0.01	48 ± 0.25
E	1.181 Max.	30 Max.
F	0.650	16.5
G	0.906	23
H	0.689	17.5
J	0.236	6

Dimensions	Inches	Millimeters
K	0.596	15
L	0.472	12
M	0.630	16
N	0.276	7
P	0.512	13
Q	0.315	8
R	0.118	3
S	0.216 Dia.	5.5 Dia.
T	M5 Metric	M5

Type	$V_{CE0(sus)}$ Volts (X 10)	Current Rating Amperes (X 10)
KD32	45	15



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

KD324515
Dual Darlington Transistor Module
 150 Amperes/600 Volts

Absolute Maximum Ratings, $T_j = 25\text{ }^\circ\text{C}$ unless otherwise specified

Ratings	Symbol	KD324515	Units
Junction Temperature	T_j	-40 to 150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 to 125	$^\circ\text{C}$
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	450	Volts
Collector-Emitter Sustaining Voltage, $V_{BE} = -2V$	$V_{CEV(sus)}$	600	Volts
Collector-Base Voltage	V_{CBO}	600	Volts
Emitter-Base Voltage	V_{EBO}	7	Volts
Collector-Emitter Voltage, $V_{BE} = -2V$	V_{CEV}	600	Volts
Continuous Collector Current	I_C	150	Amperes
Diode Forward Current	I_{FM}	150	Amperes
Continuous Base Current	I_B	9	Amperes
Diode Surge Current	I_{FSM}	1500	Amperes
Power Dissipation (Each Transistor)	P_t	690	Watts
Max. Mounting Torque M5 Terminal Screws	-	17	in.-lb.
Max. Mounting Torque M5 Mounting Screws	-	17	in.-lb.
Module Weight (Typical)	-	420	Grams
V Isolation	V_{RMS}	2500	Volts

Electrical Characteristics, $T_j = 25\text{ }^\circ\text{C}$ unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector Cutoff Current	I_{CEV}	$V_{CE} = 600V, V_{BE} = -2V$	-	-	2	mA
		$V_{CE} = 600V, V_{BE} = -2V, T_C = 125^\circ\text{C}$	-	-	15	mA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 7V$	-	-	300	mA
DC Current Gain	h_{FE}	$I_C = 150A, V_{CE} = 2V$	75	-	-	-
		$I_C = 150A, V_{CE} = 5V$	100	-	-	-
Diode Forward Voltage	V_{FM}	$I_{FM} = 150A$	-	-	1.85	Volts
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 150A, I_B = 2A$	-	-	2.0	Volts
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 150A, I_B = 2A$	-	-	2.5	Volts
Resistive	Turn-on	$V_{CC} = 300V$	-	-	2.5	μs
	Storage Time					
Switch Times	Fall Time	$I_{B1} = 2A, I_{B2} = -2A$	-	-	3.0	μs

Thermal and Mechanical Characteristics, $T_j = 25\text{ }^\circ\text{C}$ unless otherwise specified










Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Case-to-Sink	$R_{\theta(c-s)}$	Per 1/2 Module	-	-	0.1	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Case	$R_{\theta(j-c)}$	Transistor Part	-	-	0.18	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Case	$R_{\theta(j-c)}$	Diode Part	-	-	0.6	$^\circ\text{C/W}$



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272


勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

KD324515
Dual Darlington Transistor Module
 150 Amperes/600 Volts




KD324515
Dual Darlington Transistor Module
 150 Amperes/600 Volts


FORWARD BIAS SAFE OPERATING AREA (SOA)




DERATING FACTOR OF SAFE OPERATING AREA (SOA)




REVERSE RECOVERY CHARACTERISTICS OF FREE-WHEEL DIODE (TYPICAL)




DIODE FORWARD SURGE CURRENT



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (TRANSISTOR)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (DIODE)



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)