

# 10~15W AC-DC Wall Mount Universal/ America Type



80 × 55 × 30.5 mm

- Universal AC input / Full range
- 2 pole USA plug
- Class II power (without earth pin)
- Protections:  
short circuit / over load / over voltage
- RCC control, low cost for high quantity
- Approvals: UL / CSA / CE / FCC
- 1 year warranty

AC input voltage range.....	90~264VAC / 0.5A
AC inrush current.....	cold start, <20A peak@ 115VAC
Over load protection.....	hiccup mode, auto-recovery
Over voltage protection.....	clamp by zener diode > 110%
Setup, hold up time.....	200 ms, 8ms at full load and 115VAC
Withstand voltage.....	I/P-O/P:3KVAC, 1minute
Working temperature.....	0~40°C @100%, 50°C @70% load
Safety standards.....	UL 1950, CSA 22.2 approved
EMC standards.....	FCC, part 15, class B
Length of output cable.....	180cm of SPT-1, 18AWG×2C
Standard plug of DC output.....	2.1φ ×5.5φ ×11mm, center "+"

Stock No.	Type No.	Output	Tol.	R&N	Pmax.	P.P.
14251	L15D05B-P1J	5V, 2.00A	±5%	80mV	10W	16
14253	L15D12B-P1J	12V, 1.25A	±3%	100mV	15W	16
14254	L15D15B-P1J	15V, 1.00A	±3%	100mV	15W	16
14255	L15D24B-P1J	24V, 0.50A	±3%	120mV	12W	16

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)