


Red LED/Photo IC for optical link

L8045/S8046

Emitter/receiver with sleeping mode suitable for 50 Mbps optical link



L8045 and S8046 are optical communication devices designed for POF (Plastic Optical Fiber) data links. L8045 is a highly reliable, high-power LED that emits red light with a peak at 650 nm optimized for POF. A mini-lens is molded on the package for efficient coupling to a POF. When used with our recommended driver circuit, a 50 Mbps transmitter can be configured at low cost. S8046 is a high sensitivity, high-speed photo IC that receives signals at 50 Mbps and covers a wide dynamic range of 21.5 dB. The output is TTL compatible. S8046 also features a sleeping mode in which operation automatically switches to low power dissipation mode when no light is input and switches back to normal operation mode when light is input from the optical fiber. The internal IC checks which mode is currently selected and this check signal is available from the mode output terminal. Current consumption in sleeping mode is approximately 1/400th that of normal operation mode.

Features

L8045

- Peak wavelength: 650 nm
- High reliability
- High output

S8046

- Sleeping mode (low power dissipation)
- 4 to 50 Mbps
- Monolithic photo IC
- Optimum operation when used with L8045
- High reliability
- TTL output
- Wide dynamic range

Applications

- High-speed data transmission even under poor environmental conditions with high noise

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

L8045

■ Absolute maximum ratings (Ta=25 °C)

Parameter	Symbol	Value	Unit
Forward current	IF	40	mA
Reverse voltage	VR	5	V
Power dissipation *1	Pmax	250	mW
Operating temperature	Topr	-40 to +85	°C
Storage temperature	Tstg	-40 to +85	°C
Soldering	-	230 °C, 5 s, at least 1.8 mm away from package surface	


*1: Derate power dissipation at a rate of -1.75 mW/°C above Ta=25 °C

■ Electrical and optical characteristics (Ta=25 °C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Data rate	fD	NRZ	DC	-	50	Mbps
Forward voltage	VF	IF=20 mA	-	1.9	2.3	V
Reverse current	IR	VR=5 V	-	-	10	μA
Peak wavelength	λp	IF=20 mA	-	650	-	nm
Spectral half width (FWHM)	Δλ	IF=20 mA	-	20	-	nm
Fiber-coupled optical output	Po	*2, 3, 4	-13	-	-8	dBm
Rise time at pulse drive	tr	*2, 3, 4 20 to 80 %	-	-	8	ns
Fall time at pulse drive	tf	*2, 3, 4 80 to 20 %	-	-	8	ns
Pulse distortion	ΔT	*2, 3, 4	-3	-	+1	ns
Jitter	Δtj	*2, 3, 4	-	-	3	ns

*2: Input is a pseudo-random bi-phase signal at 50 Mbps.

*3: Measured with the recommended driver circuit shown below. (Measurement conditions: Vcc=4.5 to 5.5 V, R1=750 Ω, R2=2.2 kΩ, R3=22 Ω, C1=35 pF)



*4: Average value (duty ratio 50 %) measured by using a plastic fiber of φ1 mm. SI-POF and NA=0.5 (GH4001 made by Mitsubishi Rayon).

Note)

1: A bypass capacitor (0.1 μF) and another capacitor (4.7 μF) are connected between Vcc and GND at a position within 3 mm from the lead.

2: The center of the optical fiber is aligned with the center of the lens on the package. The distance between the fiber end and the lens is 0.1 mm.

SOLID STATE DIVISION

S8046

■ Absolute maximum ratings (Ta=25 °C)

Parameter	Symbol	Value	Unit
Supply voltage	Vcc	-0.5 to +7.0	V
Output voltage	Vo	-0.5 to Vcc+0.5	V
Output current	Io	10	mA
Power dissipation	P	250 *5	mW
Operating temperature	Topr	-40 to +85	°C
Storage temperature	Tstg	-40 to +85	°C
Soldering	-	230 °C, 5 s, at least 1.8 mm away from package surface	-

*5: Derate power dissipation at a rate of -1.75 mW/°C above Ta=25 °C

■ Electrical and optical characteristics (Ta=25 °C, Vcc=4.5 to 5.5 V)

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Data rate	fD	bi-phase signal	4	-	50	Mbps
Current consumption (in operation mode)	Icco	*6, 7	-	-	40	mA
Current consumption (in sleeping mode)	Iccs	Pin= -∞	-	-	100	μA
Minimum overload	Pimax	*6, 7, 9, 10	-8	-	-	dBm
Minimum receiver input power	Pimin	*6, 7, 9, 10	-	-	-29.5	dBm
Output voltage	H level output voltage	Voh loh= -150 μA *6, 7	2.7	-	-	V
	L level output voltage	Vol Iol=1.6 mA *6, 7	-	-	0.4	V
	Rise time	tr	-	-	5	ns
	Fall time	tf	-	-	5	ns
Pulse width distortion	Δt	*6, 7	-4	-	+8	ns
Jitter	Δtj	*6, 7	-	-	5	ns
Operation mode to sleeping mode switching input power	Psi	*6, 7, 9	-	-	-33	dBm
Sleeping mode to operation mode switching input power	Pop	*6, 7, 9	-	-	-30	dBm
Sleeping mode to operation mode switching time	tso	*6	-	-	200	μs
Operation mode to sleeping mode switching time	tos	*6	-	-	500	μs
Mode output	H level voltage	Vmh *11	3.0	-	-	V
	L level voltage	Vml *11	-	-	0.5	V

*6: Input is a pseudo-random bi-phase signal at 50 Mbps.

*7: CL=5 pF (including parasitic capacitance of probes, connectors and PC board)

*8: Optical input signal is generated by our standard signal generator.

*9: Average value (at 50 % duty ratio)

*10: Pe=10⁻⁹

*11: "H" in sleeping mode, "L" in operation mode


(Note)

3: A bypass capacitor (0.1 μF) and another capacitor (4.7 μF) are connected between Vcc and GND at a position within 3 mm from the lead.

4: The center of the optical fiber is aligned with the center of the lens on the package. The distance between the fiber end and the lens is 0.1 mm.


5: Output becomes undefined at a baud rate less than 4 Mbps.

■ Mode switching chart (S8046)



KPIC0066EA

■ Dimensional outline (unit: mm)



PIN No.	L8045	S8046
①	CATHODE	MODEOUT
②	CATHODE	GND
③	ANODE	Vout
④	CATHODE	Vcc

Tolerance unless otherwise noted: ±0.1, ±0.2
 Shaded area indicates burr.
 Values in parentheses indicate reference value.

KPIC0042EB

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

HAMAMATSU

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Hamamatsu City, 435-8558 Japan, Telephone: (81) 053-434-3311, Fax: (81) 053-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions.
 Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2004 Hamamatsu Photonics K.K.