

**勝特力材料 886-3-5753170**  
**勝特力电子(上海) 86-21-54151736**  
**勝特力电子(深圳) 86-755-83298787**  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## 1. FEATURES

- \* Digital display & battery operated, Inductance, Capacitance Resistance and Diode measurement.
- \* LSI-circuit provides high reliability and durability.
- \* LCD display for clear readout even in bright ambient light conditions.
- \* Input overload protection .
- \* Rotary switch function selector .
- \* Low battery indicator.

## 2. SPECIFICATIONS

### 2-1 General Specifications

Display	18 mm ( 0.7" ) LCD, Max. reading 1999.
Measurement	Inductance : 2 mH to 2 H, 5 ranges. Capacitance : 2 nF to 200 uF, 6 ranges. Resistance : 200 ohm to 20 M Ohm, 6 ranges. Diode test
Over-input indicator	" 1 " mark indication.
Sampling Time	Approx. 0.4 second.
Operating Temperature & Humidity	0 °C to 50 °C (32 °F to 122 °F). Less than 80% RH.
Power Supply	006 P DC 9V battery, heavy duty battery.
Dimensions	185 x 87 x 39 mm(7.3 x 3.4 x 1.5 inch)
Weight	280 g/0.62 LB.
Power Consumption	R measurement : Approx. 9 mA max. L & C measurement : Approx. 13 mA max.
Accessories Included	Instruction Manual ..... 1 PC Test alligator clips ..... 1 pair