



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

A HIGH-STABILITY LOAD CELLS ARE AVAILABLE FOR PRECISE MEASUREMENT OF WEIGHT.

The AA series offer high accuracy and linearity for fast, reliable measurement of electronic scale.

SPECIFICATIONS

MODEL	AAA	AAC
RATED OUTPUT	2.0mv/V 10%	
ZERO BALANCE	±5% OF R.O.	
CREEP ATRATED CAPACITY (20 Min)	0.015%	0.03% OF R.O.
NONLINEARITY HYSTERESIS AND REPEATABILITY	0.015%	0.03% OF R.O.
INPUT IMPEDANCE	400 ohm ± 15 ohm	
OUTPUT IMPEDANCE	350 ohm ± 3 ohm	
TEMPERATURE COMPENSATED	-10 TO 50	
TEMPERATURE EFFECT ON OUTPUT	0.002	0.005
	% OF APPLIED LOAD/°C	
TEMPERATURE EFFECT ON ZERO	0.004	0.01
	% OF RATED OUTPUT/°C	
SAFE OVERLOADING	1 1/2 X RATED CAPACITY	
RECOMMENDED EXCITATION	10V DC OR AC	
INSULATION RESISTANCE	> 2000 MEGOHMS	
CAPACITY	3. 6. 10. 12. 15. 20. 30. 35 KGS	

