TOWER LIGHT 多層式信號燈



勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736

胜特力电子(深圳) 86-755-83298787

Http://www. 100y. com. tw

主要特長

- 燈罩顏色有紅、黃、藍、綠或透明五種美也、鮮艷顏色。
- 只要卸下上蓋一支固定螺絲,即可自行變換顏色。
- 只要安裝一台即能掌握各機械之不同操作信號。
- 可獨立點燈或閃光來標示。
- 外型精美別緻,可自何方向明顯確認。

用途:紡織機、機械手臂(機械人)、工作母機、加工機、射出成型機等。

FEATURES:

- 1. Domes for the assorted colors: available in red, yellow, blue, green and transparent.
- 2. Easy to repair: only to loose a screw for replacing the lenses or bulbs.
- 3. Only installing one tower light: it can show thee different signals for the production flow of machine.
- 4. Two kinds of indications: by the styles of steady-burn (LT) or flashing (LTF).
- 5. With elegant design: can be clearly seen the efficiency from any directions.

Usage: Suitable for automated plant and all kinds of automatized machines:

Robot, textile machines, injection molding machines, plastic extruding machines, etc.

To indicate assorted abnormal conditions in plant equipments or automatic production lines.

Suitable for game machines: pachinko etc.

LT Specifications:

-									
Model	1 FL	2 FL	3 FL	4 FL	5 FL	Voltage		Bulb	Flash rate
LT-12	12-1	12-2	12-3	12-4	12-5	DC or AC	12V	12V 10W ①	MMMI
LT-24	24-1	24-2	24-3	24-4	24-5	DC or AC	24V	24V 10W ①	MMM.
LT-110	110-1	110-2	110-3	110-4	110-5	AC	110V	120V 10W ①	NAM.
* LT-220	220-1	220-2	220-3	220-4	220-5	AC	220V	240V 10W 🔘	WY
*" with CE a	approval	- XX	WW.3	ov.Ct		N V		ON CONTRACTIVE	

LTF Specifications:

Model	1 FL	2 FL	3 FL	4 FL	5 FL	Voltage		Bulb	Flash rate
LTF-12	12-1	12-2	12-3	12-4	12-5	DC or AC	12V	12V 10W 🔘	
LTF-24	24-1	24-2	24-3	24-4	24-5	DC or AC	24V	24V 10W 🔘	70 FPM
LTF-110	110-1	110-2	110-3	110-4	110-5	AC	110V	120V 10W 🛈	
* LTF-220	220-1	220-2	220-3	220-4	220-5	AC	220V	240V 10W 🛈	
"*" with CE approval OBA15D									