

300MHz, Low-Power, High-Output-Current, Differential Line Driver

General Description

The MAX4147 differential line driver offers high-speed performance while consuming only 100mW of power. Its amplifier has fully symmetrical inputs and outputs and uses laser-trimmed, matched, thin-film resistors to deliver 70dB CMR at 10MHz. Using current-feedback techniques, the MAX4147 achieves a 300MHz bandwidth and a 2000V/ μ s slew rate.

Optimized for differential, high-output-current applications such as transformer drivers, the MAX4147 drives ± 2.6 V into a 26.5 Ω load (single-ended) or ± 5.6 V into a 53 Ω load (differential). This device is preset for a closed-loop gain of 2V/V. Its ultra-low 0.008%/0.03 $^\circ$ differential gain/phase allow for a variety of video and RF signal-processing applications.


For power-sensitive applications, the MAX4147 has a shutdown function that reduces supply current to less than 1mA. In addition, superior SFDR (-82dBc at 10kHz, $R_L = 33\Omega$) makes it ideal as a transformer driver for HDSL applications.

For a complete differential transmission link, use the MAX4147 with the MAX4144 line receiver (see the MAX4144 data sheet for more information).

Applications

VDSL, ADSL, HDSL
 Video Twisted-Pair Driver
 Differential Pulse Amplifier
 Differential ADC Driver

Typical Application Circuit




Features

- ◆ 2V/V Fixed Gain
- ◆ 300MHz -3dB Bandwidth
- ◆ 2000V/ μ s Slew Rate
- ◆ 82dBc SFDR at 10kHz
- ◆ 70dB CMR at 10MHz
- ◆ Low Differential Gain/Phase: 0.008%/0.03 $^\circ$
- ◆ High Output Drive: ± 5.6 V into 53 Ω
- ◆ Low Power: 100mW

Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE
MAX4147ESD	-40 $^\circ$ C to +85 $^\circ$ C	14 SO

Pin Configuration



300MHz, Low-Power, High-Output-Current, Differential Line Driver

MAX4147

ABSOLUTE MAXIMUM RATINGS

Supply Voltage (V _{CC} to V _{EE})	12V	Operating Temperature Range	
Voltage on Any Input to Ground (V _{CC} + 0.3V) to (V _{EE} - 0.3V)		MAX4147ESD	-40°C to +85°C
Continuous Power Dissipation (T _A = +70°C)		Storage Temperature Range	-65°C to +160°C
SO (derate 8.33mW/°C above +70°C)	667mW	Lead Temperature (soldering, 10sec)	+300°C
Short-Circuit Duration	10sec		

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

(V_{CC} = +5V, V_{EE} = -5V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted. Typical values are at T_A = +25°C.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
DC SPECIFICATIONS						
Input Offset Voltage	V _{OS}	V _{OUT} = 0V, R _L = ∞		0.5	6	mV
Input Offset Voltage Drift	TCV _{OS}	V _{OUT} = 0V, R _L = ∞		30		μV/°C
Input Bias Current	I _B	V _{OUT} = 0V, R _L = ∞, V _{IN} = -V _{OS}		9	20	μA
Input Offset Current	I _{OS}	V _{OUT} = 0V, R _L = ∞, V _{IN} = -V _{OS}		0.03	2	μA
Input Voltage Noise	e _n	f = 10kHz		8		nV/√Hz
		f = 1MHz to 100MHz		80		μVRMS
Input Current Noise	I _n	f = 10kHz		1.7		pA/√Hz
		f = 1MHz to 100MHz		17		nARMS
Input Capacitance	C _{IN}			1		pF
Differential Input Resistance				1		MΩ
Differential Input Voltage Range		R _L = ∞	-3.6		3.6	V
Common-Mode Input Voltage Range	V _{CM}	R _L = ∞	-2.8		2.8	V
Gain	A _v	-1V ≤ V _{OUT} ≤ +1V, R _L = 53Ω		2		V/V
Gain Error		-1V ≤ V _{OUT} ≤ +1V, R _L = 53Ω		0.3	1	%
Common-Mode Rejection	CMR	V _{CM} = ±2.8V	70	100		dB
Power-Supply Rejection	PSR	V _S = ±4.5V to ±5.5V	70	100		dB
Quiescent Supply Current	I _{SY}	V _{IN} = 0, R _L = ∞		10	13	mA
Shutdown Supply Current	I _{SHDN}	V _{IN} = 0, R _L = ∞		0.6	1	mA
Output Voltage Swing	V _{OUT}	Single-ended, R _L = ∞	3.2	3.8		V
		Differential, R _L = ∞	7.2	7.8		
		Single-ended, R _L = 26.5Ω	2.2	2.6		
		Differential, R _L = 53Ω	5.0	5.6		
Output Current Drive	I _{OUT}	V _{OUT} = ±2.2V	110	160		mA
SHDN High Threshold	V _{IH}				2.0	V
SHDN Low Threshold	V _{IL}		0.8			V
SHDN Input Current	I _{SHDN}	V _{SHDN} ≤ 0.8V		75	150	μA
		V _{SHDN} ≥ 2V		10		nA

300MHz, Low-Power, High-Output-Current, Differential Line Driver

MAX4147

ELECTRICAL CHARACTERISTICS (continued)

($V_{CC} = +5V$, $V_{EE} = -5V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.)









PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
AC SPECIFICATIONS						
-3dB Bandwidth	BW(-3dB)	$V_{OUT} \leq 0.1V_{RMS}$		300		MHz
Full-Power Bandwidth	FPBW	$V_{OUT} = 2V_{p-p}$		250		MHz
0.1dB Bandwidth	BW(0.1dB)	$V_{OUT} \leq 0.1V_{RMS}$		70		MHz
Common-Mode Rejection	CMR	$f = 10MHz$		70		dB
Slew Rate	SR	Differential, $-2V \leq V_{OUT} \leq +2V$		2000		V/ μs
Settling Time	t_s	$1V \leq V_{OUT} \leq +1V$, $R_L = 150\Omega$, $Av_{CL} = +2$	to 0.1%	10		ns
			to 0.01%	30		
Differential Gain	DG	$f = 3.58MHz$, $R_L = 150\Omega$		0.008		%
Differential Phase	DP	$f = 3.58MHz$, $R_L = 150\Omega$		0.03		degrees
Spurious-Free Dynamic Range	SFDR	$f_C = 10kHz$, $V_{OUT} = 4.0V_{p-p}$, $R_L = 33\Omega$ single-ended, $R_S = 50\Omega$, Figure 1		-82		dBc
		$f_C = 5MHz$, $V_{OUT} = 2V_{p-p}$, $R_L = 150\Omega$ differential, Figure 2		-75		

300MHz, Low-Power, High-Output-Current, Differential Line Driver

MAX4147

Typical Operating Characteristics










($V_{CC} = +5V$, $V_{EE} = -5V$, $R_L = 150\Omega$, $T_A = +25^\circ C$, unless otherwise noted.)



300MHz, Low-Power, High-Output-Current, Differential Line Driver

MAX4147

Typical Operating Characteristics (continued)
 ($V_{CC} = +5V$, $V_{EE} = -5V$, $R_L = 150\Omega$, $T_A = +25^\circ C$, unless otherwise noted.)






300MHz, Low-Power, High-Output-Current, Differential Line Driver

MAX4147

Typical Operating Characteristics (continued)

($V_{CC} = +5V$, $V_{EE} = -5V$, $R_L = 150\Omega$, $T_A = +25^\circ C$, unless otherwise noted.)



Pin Description

PIN	NAME	FUNCTION
1, 7	V_{EE}	Negative Power Supply. Connect to -5V.
2	IN+	Noninverting Input
3, 5	N.C.	No Connect. Not internally connected.
4	SHDN	Logic Input for Shutdown Circuitry. A logic low enables the amplifier. A logic high disables the amplifier. The amplifier outputs are high impedance in shutdown mode; thus the impedances seen at OUT+ and OUT- are that of the feedback resistors and the protection circuitry (Figure 3).
6	IN-	Inverting Input
8, 14	V_{CC}	Positive Power Supply
9	OUT-	Inverting Output
10	SENSE-	Sense Line for the Inverting Output. Connect to OUT-, close to the pin.
11	GND	Ground
12	SENSE+	Sense Line for the Noninverting Output. Connect to OUT+, close to the pin.
13	OUT+	Noninverting Output

300MHz, Low-Power, High-Output-Current, Differential Line Driver

MAX4147




Figure 1. Single-Ended Distortion Setup




Figure 2. Differential Distortion Setup





Figure 3. MAX4147 Shutdown Equivalent Circuit

300MHz, Low-Power, High-Output-Current, Differential Line Driver

MAX4147

Package Information



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

8 _____ Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600