

MINIATURE CIRCULAR CONNECTOR

MATERIAL

INSULATOR : Thermoplastic, Glass fiber

CONTACT PIN : Phosphor Bronze

SHIELD: Brass

SPECIFICATION

CURRENT RATE : 1 AMP




INSULATION RESISTANCE : 500MΩ Min

CONTACT RESISTANCE : 30mΩ Max.



DIELECTRIC VOLTAGE : 500V AC for one minute

OPERATION TEMPERATURE : -85°C to +125°C

ORDER INFORMATION



PCB LAYOUT
(BOTTOM VIEW)



| NO. | NAME | MATERIAL | FINISH | Q'TY | REMARK |
|-----|------------|--------------|-----------------|------|---------------------------------|
| 1 | HOUSING | P.B.T. | BLACK | 1 | |
| 2 | CONTACT | PHOS. BRONZE | GOLD-TIN PLATED | 8 | N1:1~5u ; TIN:3u GOLD:1~3.4u |
| 3 | GROUND | BRASS | TIN PLATED | 1 | TIN:3~5u |
| 4 | BACK COVER | P.B.T. | BLACK | 1 | |

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)