

勝特力材料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www. 100y. com. tw

WWW.100Y.COM.

WW.100Y.COM.TW

W.100Y.COM.TW

WWW.1005

WWW.100Y.CON MODEL: MVR34 MECHANICAL DEDEODMANICE

W.1001	2. MODEL: MVR34 3. MECHANCAL PERFORMANCE	
1001	ITEM	PERFORMANCE
WW.L	FOTAL ANGLE OF ROTATION	220 ± 20 °
10	FOTATIONAL TORQUE	20~200gf.cm
	SOLDERING HEAT RESISTANCE	260 ±5°, 10 ±1 SEC

4. ELECTRIC PERFORMANCE

ITEM	PERFORMANCE
RESISTANCE RANGE	100~1M
RESISTANCE TOLERANCE	±25%
RESISTANCE TAPER	B (LINER)
RATED POWER	0.1W(AT 70)
WORKING TEMPERATURE RANGE.	-55 ~ +125
RESISTANCE TEMPERATURE COEFFICIENT	±250PPM/
MAXIMUM WORKING VOLTAGE	DC50V
ROTATIONAL LIFE	20 TURNS
RESISTANCE VARIABLE	UNDER ±15%

