



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

TECHNICAL DATA

PNP SWITCHING SILICON TRANSISTOR

Qualified per MIL-PRF-19500/350

Devices

2N3867
2N3867S

2N3868
2N3868S

Qualified Level

JAN
JANTX
JANTXV

MAXIMUM RATINGS


Ratings	Symbol	2N3867 2N3867S	2N3868 2N3868S	Unit
Collector-Emitter Voltage	V_{CEO}	40	60	Vdc
Collector-Base Voltage	V_{CBO}	40	60	Vdc
Emitter-Base Voltage	V_{EBO}	4.0		Vdc
Collector Current -- Continuous	I_C	3.0		Adc
Total Power Dissipation	P_T	@ $T_A = 25^{\circ}C^{(1)}$	1.0	W
		@ $T_C = 25^{\circ}C^{(2)}$	10	W
Operating & Storage Temperature Range	T_{OP}, T_{STG}	-55 to +200		$^{\circ}C$

THERMAL CHARACTERISTICS

Characteristics	Symbol	Max.	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	17.5	$^{\circ}C/W$

1) Derate linearly 5.71 mW/ $^{\circ}C$ for $T_A > +25^{\circ}C$

2) Derate linearly 57.1 mW/ $^{\circ}C$ for $T_C > +25^{\circ}C$



*See Appendix A for
Package Outline

ELECTRICAL CHARACTERISTICS ($T_A = 25^{\circ}C$ unless otherwise noted)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

OFF CHARACTERISTICS

Collector-Base Breakdown Voltage $I_C = 100 \mu A_{dc}$	2N3867, S 2N3868, S	$V_{(BR)CBO}$	40 60	Vdc
Collector-Emitter Breakdown Voltage $I_C = 20 mA_{dc}$	2N3867, S 2N3868, S	$V_{(BR)CEO}$	40 60	Vdc
Emitter-Base Breakdown Voltage $I_E = 100 \mu A_{dc}$		$V_{(BR)EBO}$	4.0	Vdc
Collector-Emitter Cutoff Current $V_{EB} = 2.0 V_{dc}, V_{CE} = 40 V_{dc}$ $V_{EB} = 2.0 V_{dc}, V_{CE} = 60 V_{dc}$	2N3867, S 2N3868, S	I_{CEX}	1.0 1.0	μA_{dc}
Collector-Base Cutoff Current $V_{CB} = 40 V_{dc}$ $V_{CB} = 60 V_{dc}$	2N3867, S 2N3868, S	I_{CBO}	100	μA_{dc}
Emitter-Base Cutoff Current $V_{EB} = 4 V_{dc}$		I_{EBO}	100	μA_{dc}

2N3867, S; 2N3868, S JAN SERIES

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
DC CHARACTERISTICS⁽³⁾				
Forward-Current Transfer Ratio $I_C = 500 \text{ mA}, V_{CE} = 1.0 \text{ Vdc}$ 2N3867, S 2N3868, S	h_{FE}	50		
$I_C = 1.5 \text{ A}, V_{CE} = 2.0 \text{ Vdc}$ 2N3867, S 2N3868, S		40	200	
$I_C = 2.5 \text{ A}, V_{CE} = 3.0 \text{ Vdc}$ 2N3867, S 2N3868, S		30	150	
$I_C = 3.0 \text{ A}, V_{CE} = 5.0 \text{ Vdc}$ 2N3867, S 2N3868, S		25		
$I_C = 3.0 \text{ A}, V_{CE} = 5.0 \text{ Vdc}$ All Types		20		
Collector-Emitter Saturation Voltage $I_C = 500 \text{ mA}, I_B = 50 \text{ mA}$ $I_C = 1.5 \text{ A}, I_B = 150 \text{ mA}$ $I_C = 2.5 \text{ A}, I_B = 250 \text{ mA}$	$V_{CE(sat)}$		0.5 0.75 1.5	Vdc
Base-Emitter Saturation Voltage $I_C = 500 \text{ mA}, I_B = 50 \text{ mA}$ $I_C = 1.5 \text{ A}, I_B = 150 \text{ mA}$ $I_C = 2.5 \text{ A}, I_B = 250 \text{ mA}$	$V_{BE(sat)}$	0.9	1.0 1.4 2.0	Vdc

DYNAMIC CHARACTERISTICS

Magnitude of Common Emitter Small-Signal Short Circuit Forward Current Transfer Ratio $I_C = 100 \text{ mA}, V_{CE} = 5.0 \text{ Vdc}, f = 20 \text{ MHz}$	$ h_{fe} $	3.0	12	
Output Capacitance $V_{CB} = 10 \text{ Vdc}, I_E = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{obo}		120	pF
Input Capacitance $V_{EB} = 3.0 \text{ Vdc}, I_C = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{ibo}		800	pF

SWITCHING CHARACTERISTICS

Delay Time $V_{CC} = -30 \text{ Vdc}, V_{EB} = 0,$	$I_C = 1.5 \text{ A}, I_{B1} = 150 \text{ mA}$	t_d	35	ns
Rise Time		t_r	65	ns
Storage Time $V_{CC} = -30 \text{ Vdc}, V_{EB} = 0,$	$I_C = 1.5 \text{ A}, I_{B1} = I_{B2} = 150 \text{ mA}$	t_s	500	ns
Fall Time		t_f	100	ns
Turn-On Time $V_{CC} = 30, I_C = 1.5 \text{ A}, I_B = 150 \text{ mA}$		t_{on}	100	ns
Turn-Off Time $V_{CC} = 30, I_C = 1.5 \text{ A}, I_B = 150 \text{ mA}$		t_{off}	600	ns

SAFE OPERATING AREA

DC Tests $T_C = 25^\circ\text{C}, 1 \text{ Cycle}, t = 1.0 \text{ s}$	
Test 1 $V_{CE} = 3.33 \text{ Vdc}, I_C = 3.0 \text{ A}$	
Test 2 $V_{CE} = 40 \text{ Vdc}, I_C = 160 \text{ mA}$	2N3867, S
$V_{CE} = 60 \text{ Vdc}, I_C = 80 \text{ mA}$	2N3868, S

(3) Pulse Test: Pulse Width = 300µs, Duty Cycle ≤ 2.0%.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)